

This document was generated on 01/25/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022281040

Status: Active

Overview: kk

Description: 2.54mm (.100") Pitch KK® Header, Breakaway, Right Angle, with Friction Lock, 4

Circuits, Tin (Sn) Plating

Documents:

3D Model Product Specification PS-10-07 (PDF)
Packaging Specification (PDF) RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 42228

Application Signal, Wire-to-Board

Application Tooling Part Link 011201230

Overview kk

Product Name KK®

Physical

Breakaway Yes Circuits (Loaded) 4 Circuits (maximum) 4 Color - Resin Black Durability (mating cycles max) 25 Flammability 94V-0 Glow-Wire Compliant No Lock to Mating Part Yes Material - Metal Brass Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon

Number of Rows1OrientationRight AnglePC Tail Length3.05mm (.120")

PCB Locator No PCB Retention None


PCB Thickness - Recommended 1.60mm (.063") Packaging Type Bag

Pitch - Mating Interface 2.54mm (.100")
Plating min - Mating 2.540µm (100µ")
Plating min - Termination 2.540µm (100µ")

Polarized to Mating Part
Polarized to PCB
No
Shrouded
Stackable
Temperature Range - Operating
Termination Interface: Style
Polarized to PCB
No
Partial
No
Temperature Range - Through Hole

Electrical

Current - Maximum per Contact 4A Voltage - Maximum 250V



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

42228Series

Mates With

 $\underline{2695}$, $\underline{6471}$, $\underline{7880}$, $\underline{4455}$, $\underline{7720}$

Solder Process Data

Duration at Max. Process Temperature (seconds) 5

Lead-free Process Capability Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 235

Material Info

Old Part Number 42228-0004

Reference - Drawing Numbers

Product Specification PS-10-07

Sales Drawing SD-42228-001, SD-42228-002, SD-42228-003

This document was generated on 01/25/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION