

This document was generated on 11/12/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	ap Plug Receptacle for 14-16 AWG Wire, Nylon, Fits Male Plug Diameter "), Mylar Tape Carrier	
Documents: Drawing (PDF)	RoHS Certificate of Compliance (PDF)	Series
Agency Certification CSA UL General Product Family Series Comments Crimp Quality Equipment	LR18689 E152602 Quick Disconnects <u>19039</u> Fits Male Plug Dia. 3.96mm (.156") Yes	EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status Not Reviewed Need more information on product environmental compliance?
Product Name Type Physical Barrel Type Color - Resin Flammability Gender Glow-Wire Compliant Insulation Lock to Mating Part Material - Metal Material - Metal Material - Plating Mating Material - Plating Termination Material - Plating Termination Material - Resin Orientation Packaging Type Plating min - Mating Plating min - Termination Tab Thickness Tab Width Temperature Range - Operating Termination Interface: Style Wire Insulation Diameter Wire Size AWG Wire Size mm ²	Avikrimp TM Snap Receptacle Closed Natural 94V-0 Female No Nylon (PA) None Brass Tin Tin Nylon Straight Adhesive Tape on Reel 4.064 μ m (160 μ ") 4.064 μ m (160 μ ") N/A N/A N/A Advector +105°C Crimp or Compression 3.81mm (.150") max. 14, 16 1.00 - 2.50	Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate of Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions. Search Parts in this Series <u>19039</u> Series
Electrical Voltage - Maximum Material Info Old Part Number	600V BRB-8156NT	
Reference - Drawing Numbers Sales Drawing	S SD-19039-001	

This document was generated on 11/12/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION