

This document was generated on 02/02/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status: Ac Overview: ffc	520444045 Ctive <u>fpc_throughhole</u> 25mm (.049") Right Angle, Non-ZIF, Top Contact Style Receptacle, 40 Circuits	
Documents: <u>3D Model</u> Drawing (PDF)	Product Specification PS-52044-002 (PDF) RoHS Certificate of Compliance (PDF)	Series
Agency Certification		
UL	E29179	image - Reference only
<b>General</b> Product Family Series Overview Product Name	FFC/FPC Connectors 52044 ffc_fpc_throughhole N/A	EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status
Physical Circuits (Loaded) Contact Position Entry Angle Flammability Mated Height Number of Rows Orientation PC Tail Length PCB Retention Packaging Type	40 Top 90° Angle 94V-0 5.10mm (.201") 1 Right Angle 3.50mm (.138") None Tray	Not Low-HalogenNeed more information on product environmental compliance?Email productcompliance@molex.com For a multiple part number RoHS Certificate Compliance, click herePlease visit the Contact Us section for any non-product compliance questions.
Pitch - Mating Interface Polarized to PCB Stackable Surface Mount Compatible Temperature Range - Ope Termination Interface: Styl Wire/Cable Type	erating -40°C to +85°C	Search Parts in this Series 52044Series
<b>Electrical</b> Current - Maximum per Co Voltage - Maximum	ontact 0.5A, 1A 200V	
Material Info		
Reference - Drawing Product Specification	Numbers PS-52044-002, RPS-52044-003, RPS-52044-005,	

Sales Drawing

PS-52044-002, RPS-52044-003, RPS-52044-005, RPS-52044-006, RPS-52044-008 SD-52044-\*\*45

This document was generated on 02/02/2011
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION