

- DIP sockets with increased solder tail length of 4,32, allowing application on multilayer PCBs up to 3,53mm thickness. Other lengths available upon request.
- Hi-Rel, 4-finger BeCu #30 clip rated at 3 amps. See page 208 for details.
- Uses Mill-Max #0134 pin. See page 134 for details.

Total number of pins				Quantity per tube	<h3 style="margin: 0;">Ordering Information</h3>
	A	B	C		

10	12,6	5,08	7,6	40		111-XX-210-41-001000
4	5,0	7,62	10,1	102	<div style="border: 2px solid black; border-radius: 50%; padding: 10px; display: inline-block;"> <p style="margin: 0;"><b>XX= Plating Code</b> <b>See Below</b></p> </div>	111-XX-304-41-001000
6	7,6	7,62	10,1	67		111-XX-306-41-001000
8	10,1	7,62	10,1	50		111-XX-308-41-001000
10	12,6	7,62	10,1	40		111-XX-310-41-001000
14	17,7	7,62	10,1	28		111-XX-314-41-001000
16	20,3	7,62	10,1	25		111-XX-316-41-001000
18	22,8	7,62	10,1	22		111-XX-318-41-001000
20	25,3	7,62	10,1	20		111-XX-320-41-001000
22	27,8	7,62	10,1	18		111-XX-322-41-001000
24	30,4	7,62	10,1	16		111-XX-324-41-001000
28	35,5	7,62	10,1	14		111-XX-328-41-001000
20	25,4	10,16	12,7	20		111-XX-420-41-001000
22	27,8	10,16	12,7	18		111-XX-422-41-001000
24	30,4	10,16	12,7	16		111-XX-424-41-001000
28	35,5	10,16	12,7	14		111-XX-428-41-001000
32	40,6	10,16	12,7	12		111-XX-432-41-001000
24	30,5	15,24	17,7	16		111-XX-624-41-001000
28	35,5	15,24	17,7	14		111-XX-628-41-001000
32	40,6	15,24	17,7	12		111-XX-632-41-001000
36	45,7	15,24	17,7	11		111-XX-636-41-001000
40	50,8	15,24	17,7	10	111-XX-640-41-001000	
42	53,3	15,24	17,7	9	111-XX-642-41-001000	
48	60,9	15,24	17,7	8	111-XX-648-41-001000	
50	63,5	15,24	17,7	8	111-XX-650-41-001000	
52	66,0	15,24	17,7	7	111-XX-652-41-001000	
50	63,5	22,86	25,3	8	111-XX-950-41-001000	
52	66,0	22,86	25,3	7	111-XX-952-41-001000	
64	81,2	22,86	25,3	6	111-XX-964-41-001000	

For RoHS compliance, select ◇ plating code. For the all gold option (XX=13) also change part number from 111-XX-XXX-41-001000 to 111-13-XXX-41-001100



SPECIFY PLATING CODE XX=	13 <span style="color: green;">◇</span>		93	99		43 <span style="color: green;">◇</span>	44 <span style="color: green;">◇</span>
Sleeve (Pin)	0,25µm Au		5,08µm Sn/Pb	5,08µm Sn/Pb		5,08µm Sn	5,08µm Sn
Contact (Clip)	0,76µm Au		0,76µm Au	5,08µm Sn/Pb		0,76µm Au	5,08µm Sn