



**Description**

The disposable wrist strap provides an effective, economical alternative when short-term ESD protection is required. The disposable wrist strap can be shipped with ESD-sensitive components whose manufacturer recommends that the installer of the component be grounded during installation so static discharge damage does not occur. Product is individually packaged for inclusion with customer's product if desired.

Custom printing of logo on packaging is available. Contact Customer Service for details.

**Key**

- A. 10" hypoallergenic adhesive holds conductive strip in contact with wearer. The adhesive is a waterbase acrylic.
- B. White insulative spunbonded polyester non-woven fabric outer material.
- C. Black resistive non-woven fabric provides a path to ground. Total resistance to ground is approximately 5 Megohms to limit current in the event of accidental operator contact with equipment line voltage.
- D. Release paper is removed to expose adhesive on both ends.
- E. 4" grounding end of disposable wrist strap uses adhesive to secure conductive strip to bare grounding surface. The adhesive is a waterbase acrylic.
- F. Underwriters Laboratory listing 90P1 -- rated for 250 volts AC.
- G. Packaging made with ESD Safe Dissipative Material (<math>10^{10}</math>)

Item	Description
14404	Disposable Wrist Strap



Specifications and procedures subject to change without notice

Tolerance: ± 5%



**Disposable Wrist Strap**

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](http://Desco.com)  
 PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126  
 DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407  
 PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING NUMBER**  
14404

**DATE:**  
September  
2010