



PART NO.

2318 Series

		REVISIONS						
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08

Crimp Housing






1.40 ±0.15+

0.30 ±0.05世

0.66 ±0.10-|T|-

Section : C-C





: 250V ac/dc. : 20mΩ. : $1000M\Omega$. : 1000V ac/minute.

: 3.0 A ac/dc.

RoHS


Compliant


: -40°C to +85°C. Operating temperature range Application wire : #22 to 28AWG. Materials:


Insulator : High temperature plastic (Nylon 66). Insulator colour : Black.

Contact : Phosphor bronze.

Plated : Tin Plated.







Dimensions : Millimetres

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

TOLERANCES:

DATE:
24/03/08
DATE:
24/03/08
DATE:
07/04/08

E:	DRAWING TITLE:								
08			j - Wi	re-to-B	oar	d			
E:	SIZE DWG NO.				ELECTRONIC FILE			П	REV
08	Α		M10001975		1697893-TDS_DWG				Α
TE: 08	SCALE: NTS		U.O.M.: mm		SHEET:	1	OF	3	





PART NO.


2318 Series


		REVISIONS						
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08

Accessories - Crimp Pin









Section : A-A

Specifications: Current rating

: 3.0A ac/dc. Voltage rating : 250V ac/dc. Minimum contact resistance : 20m Ω .

Withstanding voltage : $1000M\Omega$ for one minute. Withstanding voltage : 800V ac/minute. Temperature range : -25°C to +125°C. Application wires : #28 to 24AWG.

Material and Finish:

Contact : Phosphor bronze. Finish : Tin plated.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Veena	24/03/08
CHECKED BY:	DATE:
Suresh	24/03/08
APPROVED BY:	DATE:
Farnell	07/04/08

ΓE:	DRAW	ING TITLE:							
08	2.5m			m Crimp Housing - Wire-to-Board					
TE:	SIZE	DWG NO.		M10001975		CTRONIC FILE			REV
-	- A "		169		893-TDS ₋	_DW	'G	Α	
TE: 08			U.O.M.: mm		SHEET:	2	OF	3	



PART NO.

2318 Series

		REVISIONS						
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08

Specification Table

Туре	Number of Position	Α	В	Part Number
	2	2.50	6.00	2318HB-02
	3	5.00	8.50	2318HB-03
	4	7.50	11.00	2318HB-04
Crimp Housing	5	10.00	13.50	2318HB-05
Clilip Housing	6	12.50	16.00	2318HB-06
	8	17.50	21.00	2318HB-08
	10	22.50	26.00	2318HB-10
	12	27.50	31.00	2318HB-12
Crimp Pin	-	-	-	2318TB

Dimensions : Millimetres

Part Number Explanation: **Crimp Housing**

2318

HB 02 Housing Number of Positions

Number of Positions : 02 = 2, 03 = 3, 04 = 4, 05 = 5, 06 = 6, 08 = 8, 10 and 12 Positions.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

REV

Α

3 OF 3

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

	DRAWN BY:	DATE:	DRAWING TITLE		
	Veena	24/03/08			
	CHECKED BY:	DATE:	SIZE	DWG NO	
	Suresh	24/03/08	A	5	
	APPROVED BY:	DATE:	- ^ `		
	Farnell	07/04/08	SCAL	E: NTS	
-					

		re-to-B	oar	d			
SIZE A			M10001975		TRONIC FII 893-TDS_		/G
SCALE: NTS			U.O.M.: mm		SHEET:	3	OF