



by Schneider Electric

List Price \$282.00 USD

Availability **Non-Stock Item: This item is not normally stocked in our distribution facility.**

Technical Characteristics

Ampere Rating	1.0A
General Application	Short circuit and overcurrent protection
HACR Rated	Yes
Terminal Type	Line: Ring Tongue - Load: Ring Tongue
Mounting Type	Flush, Surface or DIN Rail (35mm)
Weight	10.3 Ounces
Approvals	UL489 Listed - CSA 22.2 #5.1 Certified - IEC Rated 60947-2
Marketing Trade Name	Multi 9
Enclosure Rating	IP40
Number of Poles	2-Pole
Short Circuit Current Rating	10kA@240VAC
Voltage Rating	240VAC - 125VDC
Circuit Breaker Type	Standard
For Use With	OEM Panels and Enclosures
Type	C60N
Height	4.86 Inches (124mm)
Trip Curve	C Curve - Magnetic operates between 7 to 10 times
Depth	3.00 Inches (76mm)
Width	1.42 Inches (36mm)

Shipping and Ordering

Category	00915 -
Discount Schedule	DE2
GTIN	00785901410188
Package Quantity	1
Weight	1.67 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	Y
Country of Origin	FR

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/17/2011 01:32:27