nne F		DIM"	1 X" DIM"Y"	DIM"Z"	2 ³ PCB THICKNESS			
~ +	6143	9-001 5.05 -001LF		20	3.2mm			
\bigcirc		-001LF -002 -002LF 4.25	11.7	19.2	2.4mm			
ŀ		-003 -003LF 4.55	5 11.8	18.8	2.7mm MAX.			
		-004 -004LF 5.35	5 12.6	19.6	3.5mm MAX.	120'REF.		
<u>^</u>		-005 -005LF 6.1	13.35	20.35	4±0.25 mm			
\circ						0.6 4'120'REF. 02'.6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		
	No.	DESCRIPTION	MATERIAL BRASS		FINISH	DIM"Z"REF.		
	1	SHELL			Au 0.05um MIN.			
B	2	INNER CONTAC	BERYLLIUM COPPER		Au 1.27um MIN.			
nect.c	3	OUTER CONTAC	BERYLLIUM COPPER		Au 1.27um MIN.			
	4	SPRING CLIP	BERYLLIUN	COPPER	Ni 1.27um MIN.			
\bigcirc	5	INSULATOR	PT	FE		annan att till annan ann ann ann ann ann ann ann ann		
c_	NOTE 1. FOR LEAD FREE P/N, THE PRODUCT MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 2. THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO A MANUFACTURING SOLDER PROCESS.					$0.4 \text{ Ref.} \longrightarrow 4 \text{ Ref.} \longrightarrow 5$		
					RIBED IN GS-22-008	5		
G Copyright FCI.						Itr description ecn no dr data iso 1302 Iso 1302 Iso 1302 Iso 1302 Iso 1302 METRAL JP Itr description south kr south control with		
0	form: A3		1		2			