





SMD SHIELDED POWER CHIP INDUCTOR

PCSV20

Dimensions: $\frac{\text{Inches}}{\text{(mm)}}$



Allied Part Number	Inductance (h)	Tolerance (%)	Test Freq. MHz, 200mV	RDC	Isat (mA) Typ.	Irms (mA) Typ.	Marking
PCSV20-1R0M-RC	1.0	20	1	0.17	1400	1600	A
PCSV20-1R5M-RC	1.5	20	1	0.26	1100	1400	B
PCSV20-2R2M-RC	2.2	20	1	0.32	1000	1200	C
PCSV20-3R3M-RC	3.3	20	1	0.51	820	900	D
PCSV20-4R7M-RC	4.7	20	1	0.67	680	800	E
PCSV20-5R6M-RC	5.6	20	1	0.72	650	800	F
PCSV20-6R8M-RC	6.8	20	1	0.97	560	700	G
PCSV20-100M-RC	10	20	1	1.45	470	580	H
PCSV20-220M-RC	22	20	1	2.90	310	400	I

All specifications subject to change without notice.

Features

- Magnetically Shielded Construction
- Ultra Low Profile

Electrical

Inductance Range: 1.0 μ h ~ 22 μ h (other values being added)

Tolerance: Available in 20%

Operating Temp: -25°C ~ +105°C

Isat: Current at which the Inductance will drop by no more than 30% of its initial value.

Irms: Based on a temp rise of $T = 40^\circ\text{C}$ typical at 25°C Ambient.

Resistance to Soldering Heat

Pre-Heat 150°C, 1 Min.

Solder Composition: Sn/Ag3.0/Cu0.5

Solder Temp: 260°C +/- 5°C for 10 sec

Test Equipment

(L): HP4287A + HP16197A

(RDC): Chroma MilliOhm Meter 16502

Current: HP4284A + HP42841A

Physical

Packaging: 2K per Tape and reel

Marking: As noted