



AL175ULX2

Overview

AL175ULX2 is a Two (2) Output Switching Power Supply/Charger that converts a 115VAC 60Hz input into two (2) individually PTC protected 12VDC or 24VDC outputs.

Specifications

Input:

- 115VAC 60Hz
- 10A

Output:

- 12VDC or 24VDC selectable outputs.
- 2A
- Class 2 Rated power limited outputs.
 - Fail-Safe/Fail-Secure lock output (switched).
 - Auxiliary power output (unswitched).
- 12VDC @ 2A
- 24VDC @ 1A
- 12VDC @ 1A

Battery Backup:

- 2x 12VDC 7AH gel type batteries.
- Backup when AC fails.
- 12VDC

Supervision:

- 12VDC
- 24VDC (Latching w/reset or Non-Latching).

Visual Indicators:

- 12VDC
- 24VDC

Electrical:

- 12VDC
- 24VDC
- 12VDC

Mechanical:

- 12VDC
- Accommodates up to two (2) 12VDC/7AH batteries.
- 12VDC lbs. (4.81 kg).
- 12VDC

Agency Approvals



UL 294 UL Listed for Access Control System Units.

MEA Approved

MEA - NYC Department of Buildings Approved.



CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.



CSFM - California State Fire Marshal Approved.

Enclosure Dimensions (H x W x D) (approximate):

1000000

