



AL300ULPD8R

### Overview

is a high power limited outputs.

### Specifications

#### Input:

- 100V AC @ 50/60Hz
- 100W

#### Output:

- 200mA Burglar Alarm Applications (UL 603):
- 12V = 1.0A
- 5V = 1.0A
- 3.3V @ 1.0A
- 1.5V @ 1.0A
- 0.5V @ 1.0A

#### Battery Backup:

- 12V 7Ah
  - 12V 10Ah
  - 12V 15Ah
  - 12V 20Ah
- when AC fails.

#### Supervision:

- 12V 1.0A
- 5V 1.0A
- 3.3V 1.0A
- 1.5V 1.0A
- 0.5V 1.0A

#### Visual Indicators:

- 12V 1.0A
- 5V 1.0A
- 3.3V 1.0A
- 1.5V 1.0A
- 0.5V 1.0A

#### Electrical:

- 12V 1.0A
- 5V 1.0A
- 3.3V 1.0A
- 1.5V 1.0A
- 0.5V 1.0A

#### Mechanical:

- 12V 1.0A
- 5V 1.0A
- 3.3V 1.0A
- 1.5V 1.0A
- 0.5V 1.0A

### Agency Approvals



- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems.

- UL 1069 UL Listed Hospital Signaling and Nurse Call Equipment.
- UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.

# Enclosure Dimensions (H x W x D) (approximate):

19" x 13" x 3"

