HubWayEX16S - Active UTP Transceiver Hub

Rev. DSHubWayEX16S - 10262012

Overview

HubWayEX16S

HubWay EX

HubWayEX16S Active UTP Transceiver Hub employs *automatic gain control (AGC)* to transmit UTP video and RS422/RS485 data over a single CAT-5 or higher structured cable. Unit provides 16 camera channels in a space saving 1U EIA 19” rack mount chassis which may be rack, wall or shelf mounted. Video transmission range is up to one mile max. per channel. Units are compatible with fixed or PTZ cameras.

Specifications

Input:

- [illegible]

Video:

- [illegible] up to a distance of 5000 ft. (1524m) per channel.
- [illegible]

Data:

- RS422/RS485 data inputs.

Electrical:

- [illegible]
- [illegible]
- [illegible]
- [illegible]

Features:

- Picture and Gain control.
- [illegible]
- Sixteen (16) video signal LEDs.
- [illegible] with manual reset.
- [illegible]

Accessories:

- [illegible]
  - **HubWayAv2 Slim-line -** compatible with all HubWay UTP Hubs for AC or DC fixed cameras or PTZs.
  - **HubWayDv -** compatible with all HubWay UTP Hubs for DC fixed cameras or PTZs.
  - **HubWayDvi -** built-in isolation. Compatible with all HubWay UTP Hubs for DC fixed cameras or PTZs.
- [illegible] transmission of up to four (4) video signals over a single CAT-5 or higher structured cable.

Mechanical:

- [illegible]
- [illegible]
- [illegible] x 8.5” (216mm)
- [illegible]
- [illegible]

Agency Approvals

c UL us UL Listed for Commercial CCTV Equipment (UL 2044).

Downloaded from Datasheet.su

Enclosure Dimensions *(H x W x D) (approximate)*:



Downloaded from Datasheet.su