



SPECIAL-TWEEZERS FOR SMD-TECHNIQUE

high precision tweezers from special steel
stainless – matt finish – anti-magnetic – acid-resisting
- alternative with ESD coating (-13) -



No.	Length		Finish / Model	Weight
	mm	inches		
5-048	110	4 3/8"	straight, very sharply pointed, 5 SA	12 g
5-049	110	4 3/8"	straight, very sharply pointed, 4 SA	12 g
5-049-13	110	4 3/8"	as above, with ESD coating	12 g
5-051	115	4 1/2"	straight pointed, 2 SA	15 g
5-051-13	115	4 1/2"	as above, with ESD coating	15 g
5-052	110	4 3/8"	bent, very sharply pointed, 5b SA	13 g
5-052-13	110	4 3/8"	as above, with ESD coating	13 g
5-059	120	4 3/4"	flat, rounded tips, 2.0 mm width, 2a SA	15 g
5-059-13	120	4 3/4"	as above, with ESD coating	15 g
5-078	130	5 1/8"	tapering, chisel, 1.0 mm width, PSF SA	16 g
5-078-13	130	5 1/8"	as above, with ESD coating	16 g
5-053	110	4 3/8"	obliquely angled, very sharply pointed, 51 SA	13 g
5-053-13	110	4 3/8"	as above, with ESD coating	13 g
5-054	120	4 3/4"	sickle-shape-curved, very sharply pointed, 7abb SA	16 g
5-054-13	120	4 3/4"	as above, with ESD coating	16 g
5-055	120	4 3/4"	sickle-shaped, very sharply pointed, 7a SA	15 g
5-055-13	120	4 3/4"	as above, with ESD coating	15 g
5-056	120	4 3/4"	slightly bent, very sharply pointed, 7 SA	15 g
5-056-13	120	4 3/4"	as above, with ESD coating	15 g
5-057	120	4 3/4"	self-locking, straight-pointed, 31 SA	13 g
5-058	120	4 3/4"	self-locking, bent, pointed, 31b SA	13 g
5-061	115	4 1/2"	bent, flat rounded tips, 2ab SA	16 g
5-062	115	4 1/2"	35° angled, 2.0 mm width, with gripping cavity Ø 0.8 mm, 59 SA	16 g
5-062-13	115	4 1/2"	as above, with ESD coating	16 g
5-063	115	4 1/2"	35° angled, 3.5 mm width, with gripping cavity Ø 0.8 mm, 58 SA	16 g
5-063-13	115	4 1/2"	as above, with ESD coating	16 g