



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 29.2              |
| B1  | 9.1               |
| B2  | -                 |
| C   | 55                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICKKÖRPER / GROMMET                 |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT / CONTACT PIN           |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 12  | ENDGEHÄUSE / ENDBELL                 |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

|   |
|---|
| Material Specification:                                 |
| Shell Material: Aluminium alloy                         |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere                       |
| Contact Material: Copper alloy                          |
| Contact Plating: Hard silver                            |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7188m

drawing for  
 CUSTOMER

description CA3106E14S-7P-B-F80-F0  
 Plug, straight  
 Endbell with clamp and bushing  
 AWG Crimp / Pin / Layout: 14S-7

ITT  
 Engineered for life  
 ITT CANNON GmbH  
 D-71334 Weinstadt-Germersheim

© All rights reserved. Reproduction or issue to third in any form  
 whoever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 392.12, Apr 11