




NO.	MASSE / DIMENSION
A	37.4
B	1 1/4-18UNEF-2B
C	1 1/8-18NEF-2A
D	37.7

NO.	BESCHREIBUNG / DESCRIPTION
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET
6	KONTAKTBUCHSE / CONTACT SOCKET
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm		Dimensions without tolerance indications are general tolerances in acc. with DIN7168m	drawing for
 ITT Engineered for life <small>ITT MANOMON GmbH D-71364 Heimsheim/Germany</small>		description CA3106E20-23S-F80-F42 Plug, straight without Endbell AWG Crimp / Socket / Layout: 20-23	CUSTOMER
			© All rights reserved. Reproduction or issue to third in any form whoever is only permitted with written authorization of ITT Cannon
		page 1/1 revision 302.8, Feb 11	