



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 28.8              |
| B   | 7/8-20UNEF-2B     |
| C   | 11.1              |
| D   | 3/4-20UNEF-2A     |
| E   | 9.5               |
| F   | 45                |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 14  | F-ENDGEHÄUSE / F-ENDBELL                |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification:  |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate coating over cadmium plating  |
| Insulator Material: Neoprene   |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|  |   |                         |
|--|---|-------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7188m  |   | drawing for<br>CUSTOMER |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANON GmbH<br/>D-71336 Weinstadt/Germany</small> | description CA3106F14S-5S-F80-F0  |                         |
|  | Plug, straight<br>Endbell for flex tube<br>AWG Crimp / Socket / Layout: 14S-5 |                         |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon   | page 1/1  | revision 302.8, Feb 11  |