

Local extensions

- For XT 20 and EX 20 expandable versions only (1 local extension per module)
- Millenium - Millenium local link
- Doubles the hardware and software capacities
- Transparent communication between two XT 20 units
- Max. distance between two XT 20 units : 10 metres
- Cable type : screened twisted pair



Specifications

Type	Designation	Supply	Code
XL 01	M2 - M2 local link (2 modules)	universal	88 950 200
XL 05	4 solid state outputs (8-28VDC)	universal	88 950 204
XL 06	2 relay outputs (250mA maximum)	100 → 240 V AC / 24 V AC	88 950 810

Adjacent extensions

- For XT 20 and EX 20 expandable versions only (one adjacent extension per module)
- 6 additional inputs/outputs



Specifications

Type	Designation	Supply	Code
XC 01	4 inputs PNP 2 relay outputs	24 V DC	88 950 210
	4 inputs 2 relay outputs	24 V AC	88 950 211
	4 inputs 2 relay outputs	100 - 240 V AC	88 950 212
	4 inputs 2 relay outputs	12 V DC	88 950 215
	4 inputs NPN 2 relay outputs	24 V DC	88 950 219

Communication modules

- Data communication via STN or GSM modem
- Fieldbus communication using MODBUS or ASI protocol (slave module) for XT 20 and EX 20 expandable version only (one adjacent extension per module)




Specifications

Type	Designation	Supply	Code
XC 02	AS-i communication module 24 V DC	24 V DC	88 950 213
XC 04	MODBUS communication module	24 V DC	88 950 823

Dimensions

XC 01



XC 02 - XC 04

