


# Switchcraft®

[Previous Page](#) | [Return to Index](#) | [Next Page](#)



## Q-G® CORD PLUG CONNECTORS AND RECEPTACLES

1. **T(\*)F and T(\*)FM Cord Plug With On-Off Switch**
2. **D(\*)M, D(\*)F and D(\*)FD Receptacles**

[click here to download a schematic drawing](#)

(you will need to have Adobe Acrobat installed on your system to do this)



### **T(\*)F and T(\*)FM Cord Plug With On-Off Switch**

**T(\*)F** Straight female cord plug with DPDT (2-C) locking on-off switch; standard latchlock.

**T(\*)FM** Straight female cord plug with SPDT (1-C) momentary on-off switch; standard latchlock.

Slide switches rated 500 mA, 125V (AC or DC). Mounting screws are supplied.

<b>Part Number *</b>	<b>Part Number</b>	<b>Insert Contacts</b>
T3F	☒T3FL	3
☒T3FM	☒T3FLM	3
☒T4F	☒T4FL	4
☒T4FM	☒T4FLM	4
☒T5F	☒T5FL	5
☒T5FM	☒T5FLM	5
☒T6F	☒T6FL	6
☒T6FM	☒T6FLM	6
☒T7F	-	7
☒T7FM	-	7

\* Number of insert contact or pins must be specified to complete Part Number.  
 ☒Available on special order only; contact Switchcraft for price and delivery.

### **D(\*)M, D(\*)F and D(\*)FD Receptacles**

Studio quality black and gold Q-G<sup>®</sup> receptacle with black housing and gold contacts is

designed for low/stable contact resistance and withstands corrosion where highest quality is required for recording and broadcast studio equipment, consoles, and other applications.

**D(\*)M SERIES** - Male receptacle for panel or chassis mounting. Special rectangular flange permits close spacing on crowded panels, has two .136 inch (3.45mm) diameter countersunk holes for #5-40 flat head mounting screws (not supplied). Mounts from front of panel or chassis in .766 inch (19.45) diameter hole. Satin nickel finish (Series D\*M) or black finish (Series D\*MB, or D\*MBAU).

**D(\*)F SERIES** - Female receptacle for panel or chassis mounting. Flange has two .136-inch (3.45 mm) diameter countersunk holes for #5-40 flat head mounting screws (not supplied). Mounts from front of panel or chassis in .953-inch (24.21 mm) diameter hole. Series D(\*)F has standard latchlock; Series D(\*)FD has FAS-DISCONNECT detent. Satin nickel finish (Series D\*F and D\*FD) and "Black-Velvet" finish (Series D\*FBAU).

Nickel Finish	Black Finish		Detent	QGP Series1	Pins
	Silver	Gold			
D3M	D3MB	D3MBAU	-	QGP363	3
D4M	D4MB	D4MBAU	-	-	4
D5M	D5MB	D5MBAU	-	-	5
D6M	D6MB	D6MBAU	-	-	6
D7M	D7MB	D7MBAU	-	-	7
D3F	D3FB	D3FBAU	D3FD	QGP362	3
D4F	D4FB	D4FBAU	⌘D3FDB	-	4
D5F	D5FB	D5FBAU	-	-	5
D6F	D6FB	D6FBAU	⌘D6FDB	-	6
D7F	D7FB	D7FBAU	-	-	7


\* Number of insert contact or pins must be specified to complete Part Number.

⌘ Available on special order only; contact Switchcraft for price and delivery.

1 Non-reflective gray finish, gold-plated pins.

[Previous Page](#) | [Return to Index](#) | [Next Page](#)

**To search a category please click on the corresponding icon:**



| [Connectors](#) | [Jacks and Plugs](#) |  
| [Patch Panels, Patch Kits & Jackfields](#) | [Cable Assemblies and Patch Cords](#) | [Switches](#) |

**All products shown are covered by Switchcraft's limited lifetime warranty.**

| [Switchcraft home](#) |  
[About Us](#) | [Products](#) | [What's New](#) | [Search](#) | [Contact Us](#)