



SAW Components

SAW filter

WCDMA RF

Series/type:	B3668
Ordering code:	B39202B3668U410
Date:	Jan 29, 2009
Version:	

*Appendix to Data sheet (Specifications for Huawei)

© EPCOS AG 2009. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



SAW Components

B3668

SAW filter

1950.00 MHz

Appendix to Data sheet



Characteristics

Temperature range for specification: $T = -40\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1950.0	—	MHz
Maximum insertion attenuation	α_{max}	—	3.0	3.5	dB
1920.0 ... 1980.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.5	2.1	dB
1920.0 ... 1980.0 MHz					
Return Loss		8.0	10.0	—	dB
1920.0 ... 1980.0 MHz					
Attenuation	α				dB
50.0 ... 1400.0 MHz		22.0	25.0	—	
1400.0 ... 1495.0 MHz		25.0	28.0	—	
1495.0 ... 1700.0 MHz		28.0	31.0	—	
1700.0 ... 1870.0 MHz		30.0	34.0	—	
1870.0 ... 1880.0 MHz		20.0 ¹⁾	30.0	—	
1880.0 ... 1888.0 MHz		10.0 ²⁾	23.0	—	
1888.0 MHz		10.5 ³⁾	23.2	—	
1900.0 MHz		4.5 ³⁾	8.4	—	
2000.0 MHz		4.0 ⁴⁾	6.2	—	
2000.0 ... 2015.0 MHz		3.5	6.0	—	
2012.0 ... 2015.0 MHz		7.5 ²⁾	17.0	—	
2015.0 ... 2030.0 MHz		8.0	20.0	—	
2030.0 ... 2050.0 MHz		35.0	45.0	—	
2050.0 ... 2080.0 MHz		33.0	37.0	—	
2080.0 ... 2170.0 MHz		30.0	34.0	—	
2170.0 ... 5000.0 MHz		25.0	30.0	—	
5000.0 ... 5720.0 MHz		10.0	12.0	—	
5720.0 ... 6000.0 MHz		8.0	10.0	—	
Temperature coefficient of frequency	TC_f	—	-35	—	ppm/K

1) min. 15dB ($T > 45\text{ °C}$)
 2) valid for temperature range of $-20\text{ °C to }+85\text{ °C}$
 3) valid for temperature range of $-10\text{ °C to }+80\text{ °C}$
 4) valid for temperature range of $0\text{ °C to }+80\text{ °C}$

**SAW Components****B3668****SAW filter****1950.00 MHz**

Appendix to Data sheet

**Maximum ratings**

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input power at				
1884.5 ... 1919.6 MHz	P _{IN}	19.0	dBm	Duty cycle 4:8 (100 hrs)
1884.5 ... 1919.6 MHz	P _{IN}	11.0	dBm	Duty cycle 4:8 (10,000 hrs)
2000.0 ... 2020.0 MHz	P _{IN}	10.0	dBm	CW

¹⁾ acc. to JEDEC22-A115A (machine model), 1 negative & 1 positive pulse.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2009. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

3 Jan 29, 2009



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.