



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-100-006 REV: 1.1

3.68*6.22mm Rectangular Legend LED Lamps

MODEL NO : 1003YD ECN : Page: 2/4

Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	If	25	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	85	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA
Reverse Voltage	Vr	5	V







Electronic Optical Characteristics :

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous intensity	Iv	1.0	4.0	/	mcd	If= 10 mA
Viewing Angle	2θ 1/2	/	100	/	deg	If= 20 mA
Peak Wavelength	λp	/	585	/	nm	If= 20 mA
Dominant Wavelength	λd	/	590	/	nm	If= 20 mA
Spectrum Radiation Bandwidth	Δλ	/	35	/	nm	If= 20 mA
Forward Voltage	Vf	1.7	2.0	2.4	V	If= 20 mA
Reverse Current	Ir	/	/	10	μA	Vr= 5 V



3.68*6.22mm Rectangular Legend LED Lamps

■ Typical Electro-Optical Characteristic Curves





EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-100-006 REV: 1.1

3.68*6.22mm Rectangular Legend LED Lamps

MODEL NO : 1003YD ECN : _____ Page: 4/4

■ Reliability test item and condition

No	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 20 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1