

		I					2	3 4					
	PRODUCT NO	POS	DIM F	DIM G	рім н	DIM X	DIM Y	PLATING DESCRIPTION					
	86964-X01	2X8	12.7	4.3		14	16	0 0.2µm Au					
	X02	2 X 9	7.5	3.0	6.9 3.0	14	18	PRODUCT DESCRIPTION CODE:					
	X02	2X22	11.9	1.5	8.9	42	44	XXXXX-XXXLF 2 UNASSIGNED					
А	X 0 4	2X25	11.9	1.5	8.9	48	50	LEAD FREE (SEE NOTE 5) 3 0.38µm Au	А				
	X 0 5	2X6	8.9	3.7	3.7	10	12	EXTENSION NUMBER 4 UNASSIGNED					
	X 0 6	2 X I O	10.06	0.76	7.8	18	20	NOTES TERMINAL PLATING 5 0.38µm GXT					
	X 0 7	2X25	13.45	3.0	8.9	48	50						
	X08	2 X 9	4.	7.7	4.9	16	18	I. MATERIAL BASE NOMBER					
	X09	2 X 3	8.0	2.5	4.0	4	6	BODY : GLASS FILLED NYLON UL 94V-0 BLACK	-				
	X I O X I I	2 X 4 2 X I 4	8.0 8.0	2.5	4.0	6 26	8 28	PIN : PHOSPHOR BRONZE					
	X11 X12	2 X 1 4	0.0	3.0	3.0	4	6						
	X12 X13	2 X 9	11.2	3.0	6.7	16	18	(2.) FOR DIM G OR H GREATER THAN 9.0, TOL SHALL BE					
В	X 4	2X25	7.0	1.5	4.0	48	50	2.0+0.15 ON TIP TYP & DIM X+0.25 ON TIP TYP	В				
U	X I 5	2X8	14.5	7.1	5.9	4	16	2.0-0.1 ON BASE TIF & DIM A-0.13 ON BASE TIF	U				
	X I 6	2 X I I	20.3	10.9	7.9	20	22	WHICHEVER APPLICABLE					
	X 7	2X6	8.2	3.0	3.7	10	12						
	X I 8	2XII	17.0	5.1	10.4	20	22	(3.) DIM I.O ±0.15 FOR MOLDED SIDE(S) ONLY IF SIDE(S) ARE BROKEN DIM I.5 MAX APPLIES					
	XI9	2X20	9.5	4.0	4.0	38	40						
	X 2 0	2XI4	9.5	3.0	5.0	26	28	(4.) RECESS APPLIES TO MOLDED SIDE(S) ONLY.					
	X21	2 X I 6	10.5	4.5	4.5	30	32	(5.) P/N:86964-XXXLF IS SAME AS P/N:86964-XXX. THE SUFFIX 'LF'					
	X22 X23	2X8 2X15	8.5 13.5	3.0	5.59	28	16 30	IS ADDED JUST FOR EASY LEAD FREE IDENTIFICATION.					
	X23	2 X 2	6.6		4.0	20	4	6. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK					
С	X25	2X10	6.6	1.1	4.0	18	20	TEMPERATURE FOR IO SECONDS IN A WAVE SOLDER	С				
	X26	2X25	9.5	4.0	4.0	48	50	APPLICATION WITH A 1.57MM MINIUM THICK CIRCUIT BOARD.					
U	X 2 7	2X5	7.3	1.8	4.0	8	10	7. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER					
Ľ	X28	2X8	16.5	2.5	12.5	4	16	COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.					
	X 2 9	2XI6	16.5	2.5	12.5	30	32	A BOX 8. A BOX SYMBOL WILL BE NEXT TO ANY DIMENSION. VIEW OR NOTE					
FCI.	X 3 0	2XI2	9.0	3.0	4.5	22	24	WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.					
								CONFIDENTIAL					
Copyright								www.fciconnect.com					
Сор								TOLERANCES UNLESS OTHERWISE SPECIFIED					
D								Dr BS LOW 1999-09-08 ANGULAR 0.X ± size Scale Scale<	D				
	Chr KH LEE 2010-01-09 0° ±3' 0.xxx ± ECN S10-0205 Appr JOEY NG 2010-01-09 Product family MINITEK Spec ref												
								t (2 ROWS STR) 5 BD cotolog no - CUSTOMER sheet 2 of 3					
	8EV E - 2006-03-28	l					2	3 PDM: Rev:BD stAtusReleased Printed: Oct 13, 2010					
					1								

		I					2		3 4	
[PRODUCT NO	POS	DIM F	DIM G	DIM H	DIM X	DIM Y			
	86964-X3I	2X22	7.0	1.5	4.0	42	44	-		
	X32	2X15	13.2	5.84	5.84	28	30	-		
	X 3 3	2 X I 2	8.5	3.5	3.5	22	24	-		
A	X 3 4	2X6	16.0	2.5	12.0	10	12	-		A
	X35	2X20	16.0	2.5	12.0	38	40	-		
	X 3 6	2X6	19.0	2.5	15.0	10	12			
	X 3 7	2X20	19.0	2.5	15.0	38	40	1		
	X 38	2XI6	5.5	2.0	2.0	30	32	1		
_	X 3 9	2XI7	5.5	2.0	2.0	32	34]		<u> </u>
	X 4 0	2XI6	13.45	3.0	8.9	30	32]		
	X 4 I	2X25	11.2	3.0	6.7	48	50]		
	X 4 2	2 X 4	16.5	2.5	12.5	6	8			
	X 4 3	2 X 5	12.4	2.6	8.3	8	10			
в	X 4 4	2X22	7.5	2.5	3.5	42	44			В
	X 4 5	2XI0	12.7	4.3	6.9	18	20			
	X46	2X25	7.8	2.3	4.0	48	50			
	X 4 7	2X2	7.5	2.5	3.5	2	4			
	X48	2 X 3	9.5	4.0	4.0	4	6			
	X 4 9	2X22	17.0	5.1	10.4	42	44			
	X 5 0	2X22	9.5	4.0	4.0	42	44			
	X 5 I	2X25	10.5	2.65	6.35	48	50			
	X 5 2	2 X 4	13.45	3.0	8.9	6	8			
	X 5 3	2 X 3	11.20	2.85	6.85	4	6	-		
С	X 5 4	2XI7	16.5	2.5	12.5	32	34	-		С
	X 5 5	2 X 3	10.0	Ι.Ο	7.5	4	6			ľ
J										
+ FCI									CONFIDEN	TIAL
Copyright FCI.									www.fciconnect.com surface - tolerance std projection MN 150 1302 Iso 406 ISO 1101 - ISO 406 ISO 406 ISO 406 - ISO 40	-
D									Dr BS LOW 1999-09-08 ANGULAR LINEAR 0.x ± size Size Scal 10: Chr KH LEE 2010-01-09 0" ±s" 0.xx ±0:25 A3 10:	I D 205 Rev.
										BD of 3
	FEV E - 2004-03-28	I					2		3 PDM: Rev:BD stArusReleased Printed: Oct 12	