

# 24V DRIVEN RECEIPT, TICKET PRINTER

## 3" KIOSK PRINTER UNIT

### FTP-639USL001/002

#### ■ OVERVIEW

The FTP-639USL Series is 24V driven receipt printer unit with cutter for 3 inch wide paper. The unit has our high-speed FTP-639MCL354 mechanism/cutter and control board, with an integrated paper feed and built-in paper guide section.

The receipt printer unit is most suitable for applications such as Kiosk, ATM, and receipt and ticket issuing printers for various other equipment.



#### ■ FEATURES

- Unit supported (mounting is easy)
- High speed printer (200mm / sec.)
- Auto cutter included
- Paper near end-detection function
- Paper presenter and retractor
- Up to 5 inch paper diameter
- Low power consumption
- Printer partial tilt function
- Prints 2-D barcodes

#### ■ DESIGNATION

	Item	Part Number
Printer module interface	Serial (RS-232C)	FTP-639USL001*
	USB (Ver. 1.1)	FTP-639USL002*
Cables	Serial Interface	FTP-629Y302
	USB Interface	FTP-629Y301
	Power for logic, head, motor	FTP-629Y601

\*: Interface board is FTP-629DSL100 series

## ■ SPECIFICATIONS

Item	Specifications	
Part number	FTP-639USL001/002	
Printing method	Thermal-sensitive line dot method	
Dot structure	576 dots/line	
Dot pitch (Horizontal)	0.125 mm (8 dots/mm)—Dot density	
Dot pitch (Vertical)	0.125 mm (8 dots/mm)—Line feed pitch	
Effective printing area	72 mm	
Paper width	80 <sup>+0</sup> <sub>-1</sub> mm	
Paper thickness	60 to 100 µm	
Paper print length	50 to 250mm	
Cutting type	Full or partial	
Number of columns	48 columns/line (12×24 dot font)	
Maximum printing speed	200 mm/s (1600 dotlines/s)	
Page mode	Low speed mode	40mm/sec
	Middle speed mode	80mm/sec.
	High speed mode	125 mm/sec.
	Ultra high speed mode	200 mm/sec.
Character types	Alphanumeric KANA: 159 International characters : 195 JIS KANJI (FTP-622DSL107, DSL112): approximately 6800	
Character composition, dimensions (H×W), Number of characters	24 × 12 dots, (3.0 × 1.5 mm), 48 columns 24 × 24 dots, (3.0 × 3.0 mm), 24 columns 16 × 8 dots, (2.0 × 1.0 mm), 72 columns 16 × 16 dots, (2.0 × 2.0 mm), 36 columns	
Interface	Serial RS232C, USB	
Power supply	For head	24VDC ± 5%, Voltage Current : average $\frac{1}{2}$ ( ): Peak TBA (2.04) A (at 200 mm/s printing speed, 12.5% printing ratio) TBA (1.03) A (at 80 mm/s printing speed, 12.5% printing ratio) TBA (0.51) A (at 40 mm/s printing speed, 12.5% printing ratio)
	For print motor	24VDC ± 5%, 1.0 A maximum
	For conveyance motor	24VDC ± 5%, 1.0 A maximum
	For cutter	24VDC ± 5%, 1.2 A maximum
	For logic	5VDC ± 5%, 0.2 A maximum
Dimensions	136.5(W) × 165(D) × 155 (H) mm	
Weight (mechanism, cutter, board, frame)	Approximately 1.5 kg	

(Continued)

(Continued)

Item		Specifications
Expected life	Mechanism	Pulse durability : 100 million pulse/dot (using Fujitsu's standard driving method) Wear resistance: 100 km (at 12.5% printing ratio)
	Cutter	500,000 cuts
MTBF	Mechanical	3,000 hrs
	Interface Board	500,000 cuts
Environmental conditions	Operating temperature	0°C to +50°C
	Operating humidity	20 to 85% RH (no condensation)
	Storage temperature	-20°C to +65°C (excluding paper)
	Storage humidity	5 to 90% RH (no condensation)
Detection	Head temperature	By thermistor (applied energy control, abnormal temperature detection)
	Paper out/Mark detect	By photointerrupter
	Platen open	By microswitch
	Near end paper	By mechanical switch
Recommended thermal sensitive paper		For front insertion use (80 mm width) : FTP-030P0701/P0102 Recommended papers · Oji Paper : PD150R,PD160R-N,PD170R · NIPPON Paper : TF50KS-E,TF60KS-E,TF50KS-E4 · MITSUBISHI Paper Mills : P220VBB-1,AFP-233
Paper diameter	Standard	120mm
	Extended (attachment)	TBA

\*1: 24VDC, minimum head resistance.

## ■ FUNCTIONS


	Item		Item
1.	Test print function	9.	Internal RAM abnormality detection
2.	Paper feed	10.	Cutter abnormality detection
3.	Paper out detection	11.	Mark detection
4.	Paper near end detection	12.	MCU operation abnormality detection
5.	Platen open detection	13.	Motor power saving
6.	Thermal head temperature abnormality detection	14.	Power supply disconnection protection
7.	Motor temperature detection	15.	Motor protection
8.	Voltage abnormality detection	16.	Thermal head protection

## ■ INTERFACE , COMMAND, OPTIONS

Please refer to the FTP-629DSL100 series. Interface command options, please see FTP-629DSL100 datasheet.

## ■ DIMENSIONS

Integrated unit



Note:-

- Note:**

  1. Nominal value
  2. Distance from paper roll to enclosure must be 20mm for loading.
  3. Basic reference line.

## ■ COMMANDS

Command	Contents
HT	Moves print position to the next tab.
LF	Line feed.
FF	Feeds forms (new page).
ESC FF	Data printing in page printing mode.
ESC EM+n	Setting the amount of the feeding at automatic paper feed.
ECS RS	Sets reverse printing.
ESC US	Resets reverse printing.
ESC SP+n	Character spacing setting.
ESC ! + n	Sets print mode.
ESC \$+n1+n2	Absolute position spacing.
ESC % + n	External registration character specification/cancellation.
ESC & +y+c1+c2+x+d1to dn	External registration character definition.
ESC *+m+n1+n2+d1+dN	Sets bit image mode.
ESC _ +n	Undline setting.
ESC 2	Sets 1/6 inch line feed length.
ESC 3+n	Sets the line feed length.
ESC ? + n	External registration character deletion.
ESC @	Printer initialization.
ESC A+n	Sets the space between the line.
ESC C+n	Sets the page length by character line.
ESC D+d1+dN +NUL	Sets the tab position.
ESC E+n	Highlighted printing specification/cancellation.
ESC G+n	Double printing specification/cancellation.
ESC J+n	Feeds paper in forward direction and prints.
ESC K+n	Reverse paper feed.
ESC L+n	Page printing mode selection.
ESC Q+n+!+j	Frame overlay function.
ESC R+n	Selects international character.
ESC S+n	Line printing mode.
ESC T+n	Print direction setting (only page mode).
ESC V+n	Right Rotation 90° specification / cancellation.

## Commands continued

Command	Contents
ESC W+X1+X2+1+Y2+dX1+dX2+dX1+dY2	Page printing mode printing area setting.
ESC X+m+n	Setting the turning time of the motor excitation.
ESC Y+01h+ESC+x+a+m+d~	Program download.
ESC Y+01h+ESC+x+a+m+d~	Printer test.
ESC\+n1+n2	Relative position setting.
ESC a+n	Positional alignment.
ESC c+1+n	Sets internal processing.
ESC c+4+n	Paper-out detector selection.
ESC c+5+n	Panel switch enable/disable setting.
ESC d+n	Printing and n-line feeding.
ESC e+n	Prints and reverse feeds n-lines.
ESC i	Full cut
ESC m	Partial cut
ECS s+n	Sets printing speed.
ECS t+n	Character code table selection.
ESC u+n	Status of peripherals.
ESC v	The status of the paper sensor is notified.
ESC {+n	Sets/resets upside down printing.
FS !+n	Kanji printing mode collective specification.
FS &	Kanji printing mode specification.
FS _+n	Kanji underline specification/cancellation.
FS *+ m+n1+n2+d1 to dn	High speed collective image printing specified.
FS .	Kanji printing mode cancellation.
FS 2+c1+c2+d1 to dn	External character definition.
FS 9+n	Sets the detection functions.
FS C+n	Kanji code system selection.
FS E+n	Correction of impressed energy.
FS S+n+n1+n2	Kanji spacing setting.
FS W+n	Kanji double height adn width printing specification/cancellation.
FS r+n* <sup>1</sup>	Parameter transmission.
GS ! + n	Character size specification.

## Commands continued

Command	Contents
GS \$ + n1 + n2	Vertical absolute position specification in page printing mode.
GS & +m + x + y1 + y2 + d1 to dn	Registered bit image definition.
GS' + m + n	Registered bit image printing.
GS *+x+y+d1 to dx*y*8	Registered bit image definition.
GS/ +m	Registered bit image printing.
GS :	Macro definition start/end.
GS <	Line feeds to the next mark.
GS A+m+n	Sets the line feed length after mark detection.
GS B+m	Angle setting of bar code.
GS E+n	Sets print quality.
GS H+n	HRI character printing position selection.
GS I+n+m	Printer ID registration
GS L+n1+n2	Left margin position setting.
GS R+n	Printer ID demand.
GS W + n1 + n2	Printing area width setting.
GS\ +n1 + n2	Vertical relative position specification in page printing mode (vertical direction of characters).
GS^ + r + t + m	Mark detection execution.
G a+n	Automatic notification setting status.
GS e+n+m	Sets bar code width.
GS f + n	HRI character font selection.
GS h+n	Sets bar code height.
y) GS k+m +d1to dk + NUL x) GS k+m+n+ d1 to dn	Bar code printing.
GS k+m+k1+k2+k3+k4+{[p1][d(1,1)] ~ [d(1,i)] ~ {[pi][d(i,1)]~[d(i,j)} [00]16	Print of 2Dcode (QR).
GS k+m+k1+k2+k3+k4+k5+d1~dn	Print of 2 Dcode (maxi).
GS k+m+k1+k2+k3+k4+k5+k6+d1~dn	Print of 2 Dcode (PDF417).
GS s	Check on presenter.
GS t+n	Eject paper.
GS u+n	Model selection for presenter.
GS v	Notification of firmware version.

Commands continued

Command	Contents
GS w+n	Sets bar code length.
GS x+n	Collect paper.
GS y	Eject preparation.
GS z	Retract paper.

\*<sup>1</sup>: These commands are valid with FTP-629DSL100 series.

## Fujitsu Components International Headquarter Offices

<b>Japan</b> Fujitsu Component Limited Gotanda-Chuo Building 3-5, Higashigotanda 2-chome, Shinagawa-ku Tokyo 141 8630, Japan Tel: (81-3) 5449-7010 Fax: (81-3) 5449-2626 Email: promothq@fcl.fujitsu.com Web: www.fcl.fujitsu.com	<b>Europe</b> Fujitsu Components Europe B.V. Diamantlaan 25 2132 WV Hoofddorp Netherlands Tel: (31-23) 5560910 Fax: (31-23) 5560950 Email: info@fceu.fujitsu.com Web: emea.fujitsu.com/components/
<b>North and South America</b> Fujitsu Components America, Inc. 250 E. Caribbean Drive Sunnyvale, CA 94089 U.S.A. Tel: (1-408) 745-4900 Fax: (1-408) 745-4970 Email: components@us.fujitsu.com Web: http://us.fujitsu.com/components/	<b>Asia Pacific</b> Fujitsu Components Asia Ltd. 102E Pasir Panjang Road #01-01 Citilink Warehouse Complex Singapore 118529 Tel: (65) 6375-8560 Fax: (65) 6273-3021 Email: fcal@fcal.fujitsu.com Web: http://www.fujitsu.com/sg/services/micro/components/

©2009 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.  
Rev. February 27, 2009.