




## Heyco® Nylon Push Rivets

- Rivet legs expand to securely lock components into place.
- Pull head up to release and disassemble.
- Snap into mounting holes with fingertip pressure—no tools required.

MOUNTING HOLE DIAMETER		PANEL THICKNESS				PART NO. Black	DESCRIPTION	PART DIMENSIONS								STYLE
		Minimum		Maximum				A Length		B Head Height		C Head Diameter		D Base Diameter		
in.	mm.	in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	in.	mm.	
.106	2,7	.039	1,0	.079	2,0	<b>9020</b>	PR 106-039	.126	3,2	.055	1,4	.197	5,0	.102	2,6	B
		.082	2,1	.118	3,0	<b>9022</b>	PR 106-082	.165	4,2							
		.134	3,4	.169	4,3	<b>9026</b>	PR 106-134	.217	5,5							
.122	3,1	.039	1,0	.079	2,0	<b>9028</b>	PR 122-039	.138	3,5	.063	1,6	.252	6,4	.118	3,0	B
		.079	2,0	.118	3,0	<b>9030</b>	PR 122-079	.177	4,5							
		.118	3,0	.157	4,0	<b>9032</b>	PR 122-118	.217	5,5							
		.157	4,0	.197	5,0	<b>9034</b>	PR 122-157	.256	6,5							
		.217	5,5	.256	6,5	<b>9038</b>	PR 122-217	.315	8,0							
.142	3,6	.086	2,2	.122	3,1	<b>9046</b>	PR 142-086	.177	4,5	.063	1,6	.252	6,4	.138	4,0	A
		.106	2,7	.142	3,6	<b>9048</b>	PR 142-106	.197	5,0							
		.126	3,2	.161	4,1	<b>9050</b>	PR 142-126	.217	5,5							
		.185	4,7	.220	5,6	<b>9054</b>	PR 142-185	.276	7,0							
.161	4,1	.098	2,5	.138	3,5	<b>9058</b>	PR 161-098	.197	5,0	.071	1,8	.315	8,0	.157	4,0	A
		.138	3,5	.177	4,5	<b>9060</b>	PR 161-138	.236	6,0							
		.177	4,5	.217	5,5	<b>9062</b>	PR 161-177	.276	7,0							
		.217	5,5	.256	6,5	<b>9064</b>	PR 161-217	.315	8,0							
		.295	7,5	.335	8,5	<b>9068</b>	PR 161-295	.394	10,0							
.201	5,1	.059	1,5	.098	2,5	<b>9070</b>	PR 201-059	.177	4,5	.087	2,2	.354	9,0	.197	5,0	A
		.098	2,5	.138	3,5	<b>9072</b>	PR 201-098	.217	5,5							
		.138	3,5	.177	4,5	<b>9074</b>	PR 201-138	.256	6,5							
		.177	4,5	.217	5,5	<b>9076</b>	PR 201-177	.295	7,5							
		.217	5,5	.256	6,5	<b>9078</b>	PR 201-217	.335	8,5							
		.256	6,5	.295	7,5	<b>9080</b>	PR 201-256	.374	9,5							
		.295	7,5	.335	8,5	<b>9082</b>	PR 201-295	.413	10,5							

Standard color black.



Quick Specs

**Material** Nylon 6  
**Flammability Rating** 94V-2  
**Temperature Index** 257°F (125°C)