



CATALOG LISTING	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERING DETAILS	STYLE NUMBER	CURRENT CAPACITY (AMPS)								
			RESISTIVE LOAD DC VOLTS				LAMP LOAD VDC				
102TL2-72	NONE	1	28	125	250	125	250	28 VDC	125 VDC	28 VDC	125 VDC
102TL2-72(A)	A,B,D,E,F,G,H,K,L,M,N	2	18	.75	.5	11	6	5	2	10	8
"A"		"A"									
"B"		"B"									
"D"		"D"									
"E"		"E"									
"F"		"F"									
"G"		"G"									
"H"		"H"									
"J"		"J"									
"K"		"K"									
"L"		"L"									
"M"		"M"									
"N"		"N"									
"p"		"p"									
CIRCUIT MADE WITH TOGGLE LEVER IN											
KEYWAY SIDE			CENTER			OPPOSITE KEYWAY					
MOMENTARY POSITION			MAINTAINED POSITION			MOMENTARY POSITION					

- NOTES**
- SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
 - CIRCUIT DESIGNATION, MICRO SWITCH CATALOG LISTING, AND DATE CODE ON SIDE OF SWITCH
 - FURNISHED UNASSEMBLED
 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M88723/28-20
 - KEYWAY SHOWN ON LEFT SIDE
 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE TOGGLE LOCKING
 - THE SEALING GROMMET SHALL SEAL ON A SMOOTH WIRE INSULATION OF .040 TO .083 DIAMETERS (16-20 GAGE)

DESIGN UNITS: INCH TOLERANCES UNLESS NOTED:	DRAWN: RS 28 FEB 05 CHECK: AK 28 FEB 05	WEIGHT: .135 LB MAX	REPLACES: 102TL2-70 SERIES
NO PLACE .X ± ONE PLACE .XX ± 0.030 TWO PLACE .XXX ± 0.015 THREE PLACE .XXXX ± 0.005 FOUR PLACE .XXXXX ± ANGLES ±	THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.	Honeywell	
THIRD ANGLE PROJECTION	INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY	TITLE SWITCH - TOGGLE	
	SIZE: C TYPE: I DRAWING NAME: 102TL2-72 SERIES CHART 1 REV: A	SHEET 1 OF 1	