



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: LC1200WM

Line Conditioner - Automatic voltage regulation with surge protection

Highlights

- Automatically adjusts low or high voltage
- 1200 watts continuous
- 4 NEMA 5-15R outlets
- Wallmount cabinet keeps unit conveniently out of the way
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's wall-mountable LC1200WM automatic voltage regulation system offers complete protection from brownouts, overvoltages and transient surges for computers, printers, telecommunications systems and more. Transformer-based voltage correction circuits maintain usable 120V nominal AC output during brownouts as low as 87V and overvoltages to 140V. Network grade equipment protection offers AC surge and noise suppression. Supports heavy loads up to 1200 watts. Rugged, all-metal case with keyhole mounting tabs allow secure 4-screw mounting on walls and other surfaces. Includes 4 NEMA5-15R outlets, 6-ft. line cord and lighted power switch. \$25,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

Applications

- Maintains usable output voltage during severe brownouts and overvoltages for printers, computers, telecommunications systems and more.

Package Includes

- LC1200WM Line Conditioner
- Mounting hardware
- Instruction manual

Features

- Maintains usable 120V nominal output during brownouts as low as 87V and overvoltages as high as 140V
- 1200 watts output power rating supports heavy 120V loads up to 10 amps
- All-metal case with keyhole mounting tabs for secure 4-screw mounting on walls and other surfaces
- Network grade surge suppression
- Complete EMI/RFI noise filtering
- Lighted red switch indicates power status
- 4 protected NEMA5-15R outlets
- 6-ft. AC power cord with standard NEMA5-15P input plug
- 2 year manufacturers product warranty
- \$25,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada Only)

Specifications

OUTPUT	
Output VA	1200
Output watts	1200

Output nominal voltage	120V / 60Hz
Outlet quantity / type	4 NEMA 5-15R
INPUT	
Input cord length (ft.)	6
Input cord length (m)	1.83
LEDS ALARMS & SWITCHES	
Front panel LEDs	Lighted power switch shows incoming power status
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	1200 joules
EMI / RFI AC noise suppression	80 dB
PHYSICAL	
Shipping weight (lbs)	16.00
Shipping weight (kg)	7.26
Unit Dimensions (HWD/in)	5 x 5 x 7.25
Material of construction	Steel
Form factors supported	Short tower format with keyhole slots for wall-mount applications
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=213.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.