

0291	0293	0287	0285
<p><b>0291-0-15-XX-16-XX-10-0</b> Hex press-fit in .067 plated thru hole</p>	<p><b>0293-0-15-XX-16-XX-10-0</b> Press-fit in .067 mounting hole</p>	<p><b>0287-0-15-XX-16-XX-10-0</b> Solder mount in .065 min. mounting hole</p>	<p><b>0285-0-15-XX-16-XX-10-0</b> Solder mount in .065 min. mounting hole</p>
0284	8114	0407	0415
<p><b>0284-0-15-XX-16-XX-10-0</b> Solder mount in .070 min. mounting hole</p>	<p><b>8114-0-15-XX-16-XX-04-0</b> Press-fit from underside of pc board into .065 mounting hole</p>	<p><b>0407-0-15-XX-16-XX-04-0</b> Press-fit in .066 mounting hole</p>	<p><b>0415-0-15-XX-16-XX-10-0</b> Solder mount in .063 min. mounting hole</p>
0303	0306	0273	7520
<p><b>0303-0-19-XX-16-XX-10-0</b> Wire Termination Press-fit in .067 mounting hole</p>	<p><b>0306-0-19-XX-16-XX-10-0</b> Wire Termination #18 gage crimp barrel</p>	<p><b>0273-0-15-XX-16-XX-10-0</b> Press-fit in .078 mounting hole</p>	<p><b>7520-0-15-XX-16-XX-10-0</b> Press-fit in .066 mounting hole</p>
<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b> <b>TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL <b>15</b> 10μ" GOLD OVER NICKEL</p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL <b>14</b> 10μ" GOLD OVER NICKEL <b>27</b> 30μ" GOLD OVER NICKEL</p> <p style="text-align: center;">↑ <b>CONTACT</b> #16 CONTACT (DATA ON PAGE 210)</p>		