



2501



- X -	Board Thickness	Length V
1	0,79	1,98
2	1,57	2,77
3	2,39	3,56
4	3,18	4,34

2501-X-00-XX-00-00-07-0
Swage mount in 2,39 hole


2703



- X -	Board Thickness	Length V
1	0,79	1,96
2	1,57	2,72
3	2,39	3,48
4	3,18	4,24

2703-X-00-XX-00-00-07-0
Swage mount in 2,39 hole


2702



- X -	Board Thickness	Length V	Depth D
1	0,79	1,91	1,60
2	1,57	2,67	2,36
3	2,39	3,43	
4	3,18	4,19	

2702-X-00-XX-00-00-07-0
Swage mount in 2,39 hole



2710



- X -	Board Thickness	Length V
1	0,79	1,57
2	1,57	2,39
3	2,39	3,18
4	3,18	3,96

2710-X-00-XX-00-00-07-0
Swage mount in 2,39 hole

2717/2713



- X -	Board Thickness	Length V
1	0,79	1,57
2	1,57	2,39
3	2,39	3,18
4	3,18	3,96

2717-X-00-XX-00-00-07-0
Swage mount in 2,39 hole

2713-X-00-XX-00-00-07-0
Swage mount in 2,39 hole

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
Swage pins are annealed

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: ±0,13
DIAMETERS: ±0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 5,08 m TIN/LEAD OVER NICKEL
- ◇ 80 5,08 m TIN OVER NICKEL (RoHS)
- ◇ 44 7,62 m SILVER OVER COPPER (RoHS)
- ◇ 50 7,62 m ELECTRO-SOLDER (RoHS) (60/40 SnPb)

