

This document was generated on 12/07/2009

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status: Coverview: Cov	D015475124 Active C-Grid® / SL™ Products 2.54mm (.100") Pitch SL™ FFC/FPC Connector - Single Row Male \ Circuits	/ersion D, 12
Documents: 3D Model Drawing (PDF)	Product Specification PS-70431 (PI RoHS Certificate of Compliance (PI	
General		Series image - Reference only
Product Family	FFC/FPC Connectors	
Series	70431	EU RoHS China RoHS
Comments	Male	ELV and RoHS
Overview	C-Grid® / SL [™] Products	Compliant
Product Name	<u>SI™</u>	REACH SVHC
1 loudot Name	0L	Contains SVHC: No
Physical		Halogen-Free
Circuits (Loaded)	12	Status
Contact Position	N/A	Not Reviewed
Durability (mating cycles	max) 50	Need more information on product
Entry Angle	Vertical	environmental compliance?
Flammability	94V-0	P
Number of Rows	1	Email productcompliance@molex.com
Orientation	Vertical	Please visit the Contact Us section for any
PCB Locator	No	non-product compliance questions.
PCB Retention	None	
Packaging Type	Tube	
Pitch - Mating Interface (
Pitch - Mating Interface (Search Parts in this Series
Polarized to PCB	No	70431 Series
Stackable	Yes	
Surface Mount Compatit		Application Tooling FAQ
Temperature Range - Op		Tooling specifications and manuals are
Termination Interface: St		found by selecting the products below.
Wire/Cable Type	FFC/FPC	Crimp Height Specifications are then
Electrical		contained in the Application Tooling
CSA	LR19980	Specification document.
Current - Maximum	2A	Global
UL	E29179	Description Product #
Voltage - Maximum	250V	Standard Manual 0622007800
Material Info	2007	Press for FFC Tool Kit for Standard <u>0622007400</u>
Reference - Drawing N	umbers	Manual Press FFC
Product Specification	PS-70431	
Sales Drawing	SDA-70431-****	
Sales Drawing	SDA-70431-0421-0444	

This document was generated on 12/07/2009
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION