

This document was generated on 04/08/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 15166-1049 Status: Active

Premo-Flex™ FFC and Etched Polyimide Jumpers Overview:

0.50mm Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 33 Circuits, **Description:**

0.254m Cable Length, Cable Thickness 0.12mm, Tin (Sn) Plating

Documents:

Drawing (PDF) Packaging Specification PK-15166-001 (PDF) Product Specification PS-15166-001 (PDF) RoHS Certificate of Compliance (PDF)

General

Product Family Cable 15166 Series

Comments Contacts on the same side, Type A

Crimp Quality Equipment Yes

Overview Premo-Flex™ FFC and Etched Polyimide Jumpers

Premo-Flex™FFC Jumper **Product Name**

UPC 884982850781

Physical

Cable Length 0.254m Circuits (Loaded) 33 Circuits (maximum) 33 Net Weight 1.000/g Bag Packaging Type Pitch - Termination Interface 0.50mm Temperature Range - Operating -40°C to +105°C

Wire Size AWG N/A

Wire/Cable Type Flat Flex Cable

Electrical

Current - Maximum per Contact 0.5A Voltage - Maximum 60V AC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-15166-001 **Product Specification** PS-15166-001 Sales Drawing SD-15166-001

Series image - Reference only

EU RoHS China RoHS **ELV and RoHS** Compliant

REACH SVHC Not Reviewed

Low-Halogen Status **Not Reviewed**

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

15166Series

Use With

www.molex.com/product/ffcfpc_th.html

This document was generated on 04/08/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION