


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 2-18NS-2A         |
| B   | 22.2              |
| C   | 4                 |
| D   | 34.2              |
| E   | 47.6              |
| F   | 44.5              |
| G   | 57                |
| H   | 4.4               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

**Material Specification:**  
 Shell Material: Aluminium alloy  
 Shell Plating: Olive drab chromate coating over cadmium plating  
 Insulator Material: Neoprene  
 Contact Material: Copper alloy  
 Contact Plating: Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN 7168m  
 drawing for CUSTOMER

**ITT**  
 Engineered for life  
 ITT SPANISH GROUP  
 21708 Huesped-Guerrero

description MS3102E32-7PW  
 Box mounting receptacle

Solder Cup / Pin / Layout: 32-7

© All rights reserved. Reproduction or reuse in any form without written authorization of ITT Cannon. page 1/1 revision 302.8, Feb 11