


NO.	MASSE / DIMENSION
A	37.4
B	1 1/4-18NEF-2B
C	1 3/16-18NEF-2A
D	37.5
E	22.0
F	29.5

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICKTÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING
12	ENDGEHÄUSE / ENDBELL



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate coating over cadmium plating
Insulator Material: Neoprene
Contact Material: Copper alloy
Contact Plating: Hard silver

all dimensions are in mm		drawing for CUSTOMER	
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m			
 <b>ITT</b> <i>Engineered for life</i> <small>ITT CANON GmbH</small> <small>91128 Weisbach Germany</small>	description	MS3108R20-29P	
	Plug 90° Shortened light-weight endbell without cable clamp Solder Cup / Pin / Layout: 20-29		
<small>© All rights reserved. Reproduction or issue in any form without written authorization of ITT Canon</small>		page	1/1
		revision	302.8, Feb 11