


### MT1275 Series

Specifications:

Parameters	Units	MB1275A01NP	MB1275A03NP	MB1275A05NP	MB1275A12NP
▶ Min Sound Pressure Level at 10cm	dBA	75	83	83	83
Rated Voltage	Vdc	1.5	3	5	12
Operating Voltage	Vdc	1.4 - 2	2 - 5	3 - 7	9 - 15
Resonance Frequency	Hz	2300 ± 500	2300 ± 400	2300 ± 300	2300 ± 400
▶ Max Operating Current	mA	25	25	30	25
Tone	-	Continuous	Continuous	Continuous	Continuous
Operating Temperature	°C	-20 - +70	-20 - +70	-20 - +70	-20 - +70
Case Material	-	Noryl	Noryl	Noryl	Noryl
Weight	g	2.0	2.0	2.0	2.0



\* Washable

Specifications:

Parameters	Units	MB1275B01NP	MB1275B03NP	MB1275B05NP	MB1275B12NP
▶ Min Sound Pressure Level at 10cm	dBA	75	83	83	83
Rated Voltage	Vdc	1.5	3	5	12
Operating Voltage	Vdc	1.4 - 2	2 - 5	3 - 7	9 - 15
Resonance Frequency	Hz	3100 ± 300	3100 ± 300	3100 ± 300	3100 ± 300
▶ Max Operating Current	mA	25	25	30	30
Tone	-	Continuous	Continuous	Continuous	Continuous
Operating Temperature	°C	-20 - +70	-20 - +70	-20 - +70	-20 - +70
Case Material	-	Noryl	Noryl	Noryl	Noryl
Weight	g	2.0	2.0	2.0	2.0

Unit: mm • Tolerance: ±0.5mm

▶ Value applying rated voltage

