

RT-375

*Clear, flame-resistant,
flexible, fluoropolymer tubing*



Applications

Protects wire and cable markers subject to extreme abuse, while permitting full inspectability of each item covered. Provides bundling and jacketing of wires and cables, protecting them from mechanical and chemical abuse. Protects electronic components while permitting their identification and inspection.

Operating temperature range

-55°C to 150°C

Features and benefits

- 2:1 shrink ratio.
- Exceptional clarity and clarity stability.
- Toughness, chemical resistance, and high-temperature performance.
- High flame-resistance.
- Approximately 40 percent thinner walls than most general purpose polyolefin tubings.
- Recommended maximum temperature for use as a primary insulator: 135°C.

Installation

Minimum shrink temperature: 125°C

Minimum full recovery temperature: 150°C

Available in:



Americas

Europe

Asia Pacific



Specifications/approvals

Series	 UL	 CSA	Military	Raychem
RT-375	E85381 WW-1 600 V, 150°C	LR31929 WW-1 600 V, 150°C	AMSDTL-23053/18*, Class 2	RT-375

*Formerly MIL-I-23053/18 and MIL-DTL-23053/18.

Fax-on-demand	Fax ID	Description
US only (800) 260-9099	2170	Data sheet
Outside US (650) 257-2301	2171	RT-375

Visit our website at www.tycoelectronics.com

Product dimensions (mm/in)

Size	Inside diameter		Recovered wall thickness**
	Minimum expanded as supplied	Maximum recovered after heating	After heating
3/64	1.2 (0.046)	0.6 (0.023)	0.25 ± 0.05 (0.010 ± 0.002)
1/16	1.6 (0.063)	0.8 (0.031)	0.25 ± 0.05 (0.010 ± 0.002)
3/32	2.4 (0.093)	1.2 (0.046)	0.25 ± 0.05 (0.010 ± 0.002)
1/8	3.2 (0.125)	1.6 (0.062)	0.25 ± 0.05 (0.010 ± 0.002)
3/16	4.8 (0.187)	2.4 (0.093)	0.25 ± 0.05 (0.010 ± 0.002)
1/4	6.4 (0.250)	3.2 (0.125)	0.30 ± 0.08 (0.012 ± 0.003)
3/8	9.5 (0.375)	4.8 (0.187)	0.30 ± 0.08 (0.012 ± 0.003)
1/2	12.7 (0.500)	6.4 (0.250)	0.30 ± 0.08 (0.012 ± 0.003)
3/4	19.1 (0.750)	9.5 (0.375)	0.43 ± 0.08 (0.012 ± 0.003)
1	25.4 (1.000)	12.7 (0.500)	0.48 ± 0.08 (0.012 ± 0.003)

**Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering information

Color	Standard Clear (-X)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.
Standard packaging	On spools.
Ordering description***	Specify product name, size and color (for example, RT-375 1/4-X).

***Europe only. For supply to MIL, Def Stan and BS add -MS, -DS or -BS to ordering description.