


<b>TITLE</b> LM259X Inductor 220 $\mu$ Hy .51 ADC	 1000 PARKERS LAKE ROAD WAYZATA, MN 55391	<b>AGENCY APPROVAL:</b> N/A	<b>PARTNUMBER</b> 34590 REV C    PAGE 1								
Old Schott P/N: 67144420											
<b>ELECTRICAL CHARACTERISTICS</b> Specifications at room temperature (ref. 25°C)											
<b>GENERAL NOTES:</b> <ol style="list-style-type: none"> <li>Current rating is the current at which the inductance is a minimum of 90% of the rated value.</li> <li>All pins may not be used; electrical schematic is based on the standard footprint.</li> </ol>	<p style="text-align: center;"><b>TERMINLS:</b> .012 X .028</p> <p>Jumper terminals on PC Board. 1,2,3,4</p> <p>Jumper terminals on PC Board. 5,6,7,8</p> <table border="1" data-bbox="1078 1472 1435 1522"> <thead> <tr> <th>TOLERANCES UNLESS OTHERWISE NOTED</th> <th>2 PLACE</th> <th>3 PLACE</th> <th>ANGLE</th> </tr> </thead> <tbody> <tr> <td></td> <td>+ .03</td> <td>+ .010</td> <td>+ °</td> </tr> </tbody> </table>			TOLERANCES UNLESS OTHERWISE NOTED	2 PLACE	3 PLACE	ANGLE		+ .03	+ .010	+ °
TOLERANCES UNLESS OTHERWISE NOTED	2 PLACE	3 PLACE	ANGLE								
	+ .03	+ .010	+ °								