

## METER COIL RESISTANCE

| Ω<br>RANGE | ITEM  |       |       |        |
|------------|-------|-------|-------|--------|
|            | SD-38 | SD-60 | SD-80 | SD-506 |
| DC 100uA   | 1500Ω | 1500Ω | 1500Ω |        |
| DC 1mA     | 40Ω   | 40Ω   | 40Ω   |        |
| DC 20mA    | 40Ω   | 40Ω   |       |        |
| DC 500mA   | 40Ω   |       |       |        |
| DC 1A      | 6Ω    | 6Ω    | 6Ω    |        |
| DC 3A      | 6Ω    |       |       |        |
| DC 5A      | 6Ω    | 6Ω    | 6Ω    | 0.01Ω  |
| DC 10A     |       | 6Ω    | 6Ω    | 0.01Ω  |
| DC 15A     |       | 6Ω    |       | 0.01Ω  |
| DC 20A     |       |       |       | 0.01Ω  |
| DC 30A     |       | 6Ω    | 6Ω    |        |
| DC 50A     |       | 6Ω    | 6Ω    |        |
| DC 12V     |       |       |       | 1.3KΩ  |
| DC 15V     | 40Ω   | 40Ω   | 40Ω   | 2.3KΩ  |
| DC 24V     |       |       |       | 3KΩ    |
| DC 30V     | 40Ω   | 40Ω   | 40Ω   | 3KΩ    |
| DC 300V    |       | 40Ω   | 40Ω   |        |

\*\*P.S. \*\* SD-301 : 650Ω±10%, 500uA ±15% (STANDARD) OR  
ACCORDING TO YOUR SPECIFICATION.

## THREAD SIZE OF SCREWS

|   | SD-38         | SD-60         | SD-80        |
|---|---------------|---------------|--------------|
| A | 3 x 5 , P:0.5 | 5/32x1/4, 32W | 5mm, P: 0.9  |
| B | 2.3x12, P:0.4 | 1/8x1/2, 40W  | 1/8x1/2, 40W |

A : INPUT TERMINALS

B : FOUR LEGS FOR INSTALLATION