



PIN ASSIGNMENT

CN1				CN2		
No.	SYMBOL	No.	SYMBOL	No.	SYMBOL	CABLE COLOR
1	GND	17	G4	1	ANODE1	BLACK
2	CK	18	G5	2	ANODE2	RED
3	HSYC	19	GND	3	ANODE3	WHITE
4	VSYC	20	B0	4	CATHODE1	BLACK
5	GND	21	B1	5	CATHODE2	RED
6	R0	22	B2	6	CATHODE3	WHITE
7	R1	23	B3			
8	R2	24	B4			
9	R3	25	B5			
10	R4	26	GND			
11	R5	27	ENAB			
12	GND	28	VCC1(3.3V)			
13	G0	29	VCC2(3.3V)			
14	G1	30	R/L			
15	G2	31	U/D			
16	G3	32	NC			
		33	GND			

NOTES
 1. THE DIMENSIONS WITH THE MARK (●) ARE CONTROLLED AS A PARTICULAR CHARACTERISTIC.
 2. TOLERANCE WITHOUT INDICATION: ±0.5

TOLERANCE			
MEASURE	A	B	C
L416	±0.1	±0.3	±1
164(L63)	±0.2	±0.5	±1.5
63(L+250)	±0.3	±0.8	±3
250(L+500)	±0.5	±1.2	±5
500(L)	±0.8	±2	±10
ANGLE	±1°	±5°	±10°

MATERIAL:	FINISH:
DATE 2010/06/03	THIRD ANGLE PROJECTION
DRAWN Noboru Wada	TITLE DIMENSIONAL OUTLINE
CHECKED Yasuo Yamaguchi	DWG NO(CODE) T-55285AD base
DATE 2010/07/10	DWG SIZE A2
DESIGN S. Sano	DWG REV 0