**Ouick Links** 

Search by Keyword or Part #

Check Pricing & Availability Search for Tooling

Contact Us About This Product

Product Feature Selector

**Products** 

Documentation

Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Relays</u> > <u>Product Feature Selector</u> > Product Details

## 7012NK Product Details



7012NK

(1-1423159-0)TE Internal Number: 1-1423159-0 

#### Time Delay Relays

Not EU RoHS or ELV Compliant

#### **Product Highlights:**

- 7000 Electropneumatic Timing Industrial Series Input Voltage = 48 VDC Contact Arrangement = 2 Form C, DPDT, 2 C/O Contact Rating = 10A @ 240 VAC
- Mounting Options = Panel Mount

View all Features









## **Documentation & Additional Information**

#### **Product Drawings:**

None Available

## Catalog Pages/Data Sheets:

## **Product Specifications:**

None Available

## **Application Specifications:**

None Available

#### Instruction Sheets:

• 7000 Series 2-Pole Timing Relay (PDF, English)

#### **CAD Files:**

• None Available

# **Additional Information:**

Product Line Information

## Related Products:

Tooling

## Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

Termination Type = Screw Terminal

## **Electrical Characteristics:**

- Input Voltage (VDC) = 48
- Contact Rating = 10A @ 240 VAC

Body Related Features:

• Series = 7000 Electropneumatic Timing - Industrial

## **Contact Related Features:**

- Mounting Options = Panel Mount
- Mode of Operation = On-Delay
- Delay Time = 1 second to 300 seconds
- Type of Control = Knob
- Repeatability, Max. = ± 10%
- Approved Standards = CE Approved, CSA Certified, FM Approved, UL Listed
- Approx. Dimensions (L x W x H) (mm [in]) =  $114.80 \times 65.30 \times 71.90$ [4.523 x 2.572 x 2.832]

## **Configuration Related Features:**

- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

#### Industry Standards:

List all Documents

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

## Conditions for Usage:

• Temperature Range (?C) = -30 - +75

### Other:

• Brand = Agastat

**Corporate Information Quick Links Customer Support** Who We Are Check Distributor Inventory Email or Chat with Us Investors Find a Phone Number Cross Reference News Room Find Documents & Drawings Supplier Portal Product Compliance Support Center

Careers Site Map Search Knowledge Base

Manage Your Account

<page-header> Provide Website Feedback

© 2009 Tyco Electronics All Rights Reserved | Privacy Policy