		Corporate Home	Electronic C	Components Segmen	ts Who We Are	2
						<u>My Accour</u>
- Тусс	Electronics	Our commitment. Yo	ur advantage.			Search
Products	Documentation	Resources My A	Account Cu	istomer Support		
<u>-lome</u> > <u>Prod</u>	lucts > <u>By Type</u> > <u>Resist</u>	ors > Product Feature S	<u>Selector</u> > Produ	uct Details		
<u> RG060 :</u>	3F1K0/10 Pro	oduct Details				
						Live Product Chat
		Fixed Resistors				Quick Links
	22	<u>Converted to EU Ro</u>	<u>HS/ELV Complia</u>	ant (Statement of Compl	iance)	<u>Check Pricing & Availability</u> <u>Search for Tooling</u>
		Product Highlights: Resistor Type = Ger 	neral Purnose R	esistor		Product Feature Selector Contact Us About This Product
A	360	 Resistance Selection Resistance = 1K ? 				
		 Power Rating = .10 Tolerance = 1 % 	W			
	603F1K0/10 622866-2)	 Tolerance = 1 % View all Features 				
	Number: 1622866-2					
	Active	Add to My Part List	Request Sa	mple 🍈 Find Similar Pr	oducts 🥂 Bu	<u>y Product</u>
	tion & Additional Info	rmation				6
 Product Drawings: <u>THICK FILM CHIP RESISTORS SERIES CRG 0603</u> (PDF, English) 					Additional Information: Product Line Information	
Catalog Pages/Data Sheets:					Additional Product Images:	
• Thick Film Precision Chip Resistors - Type CRG Serie (PDF, English)					• <u>Pad Layout</u>	
Product Specifications: • None Available					Related Products: • Tooling	
None Available					• <u>roomg</u>	
	Specifications: Available					
Instruction	Shoota					
	Available					
CAD Files:						
• None	Available					
	Available			List all Documents		
	Available			List all Documents		
None	atures (Please use the P	roduct Drawing for all d	lesign activity)	1		
None			lesign activity)	Industry Standards		compliant, ELV compliant
None Product Fea Product Typ Resist Resist	atures (Please use the P pe Features: for Type = General Purpo tance (?) = 1K		lesign activity)	Industry Standards RoHS/ELV Com Lead Free Sold 	<u>pliance</u> = RoHS er Processes =	Reflow solder capable to 245?C,
None None Product Fea Product Typ Resist <u>Resist Eleme</u>	atures (Please use the P pe Features: for Type = General Purpo		lesign activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com	<u>pliance</u> = RoHS er Processes = apable to 260?0	Reflow solder capable to 245?C,
None None Product Fea Product Ty Resist Resist Eleme Termin	atures (Please use the P pe Features: for Type = General Purpo cance (?) = 1K ent = Thick Film nation Type = Solder		design activity)	Industry Standards RoHS/ELV Com Lead Free Sold Reflow solder c	<u>pliance</u> = RoHS er Processes = apable to 260?0	Reflow solder capable to 245?C,
None None Product Fea Product Ty Resist Resist Eleme Termin Electrical C Resist	atures (Please use the P pe Features: for Type = General Purpo tance (?) = 1K ant = Thick Film nation Type = Solder Characteristics: tance Selection (?) = K		design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive Conditions for Usag	pliance = RoHS er Processes = apable to 260?C pliance History e:	Reflow solder capable to 245?C, = Converted to comply with RoHS
None None Product Fea Product Ty Resist Resist Eleme Termin Electrical C Resist Power	atures (Please use the P pe Features: for Type = General Purpo fance (?) = 1K fint = Thick Film nation Type = Solder Characteristics: fance Selection (?) = K Chating (W) = 0.10		design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive	pliance = RoHS er Processes = apable to 260?C pliance History e:	Reflow solder capable to 245?C, = Converted to comply with RoHS
None None None Product Fea Product Ty Resist Resist Eleme Termin Electrical C Resist Power Tolera	atures (Please use the P pe Features: for Type = General Purpo tance (?) = 1K ant = Thick Film nation Type = Solder Characteristics: tance Selection (?) = K	ose Resistor	design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive Conditions for Usag	pliance = RoHS er Processes = apable to 260?C pliance History e: oefficient (ppm/ ion:	Reflow solder capable to 245?C, = Converted to comply with RoHS
None None None Product Fea Product Ty Resist Eleme Termin Electrical C Resist Power Tolera Packa	atures (Please use the P pe Features: or Type = General Purpo cance (?) = 1K ent = Thick Film nation Type = Solder Characteristics: cance Selection (?) = K C Rating (W) = 0.10 ence (%) = 1	ose Resistor	design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive Conditions for Usag • Temperature C Operation/Applicat • Application = V	pliance = RoHS er Processes = apable to 260?C pliance History e: oefficient (ppm/ ion:	Reflow solder capable to 245?C, = Converted to comply with RoHS
None None	atures (Please use the P pe Features: for Type = General Purport ance (?) = 1K ant = Thick Film nation Type = Solder Characteristics: ance Selection (?) = K Rating (W) = 0.10 ance (%) = 1 ge Type = Taped and Re ance Features: a = CRG	ose Resistor	design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive Conditions for Usag • Temperature C Operation/Applicat	pliance = RoHS er Processes = apable to 260?C pliance History e: oefficient (ppm/ ion: arious	Reflow solder capable to 245?C, = Converted to comply with RoHS
None None	atures (Please use the P pe Features: for Type = General Purpo fance (?) = 1K ant = Thick Film nation Type = Solder Characteristics: fance Selection (?) = K Rating (W) = 0.10 ance (%) = 1 ge Type = Taped and Re ed Features:	ose Resistor	design activity)	Industry Standards • RoHS/ELV Com • Lead Free Sold Reflow solder c • RoHS/ELV Com directive Conditions for Usag • Temperature C Operation/Applicat • Application = V Other:	pliance = RoHS er Processes = apable to 260?C pliance History e: oefficient (ppm/ ion: arious	Reflow solder capable to 245?C, = Converted to comply with RoHS