

# RFID Systems Product Specifications



## HF Reader ICs

| Part Number             | TRF7960   | TRF7961   |
|-------------------------|---|---|
| Operating Frequency     | 13.56MHz  | 13.56MHz  |
| Supported Protocols     | ISO 15693<br>ISO 18000-3 (Mode 1)<br>ISO 14443A & B<br>Tag-It™ HF   | ISO 15693<br>ISO 18000-3 (Mode 1)<br>Tag-It™ HF   |
| Operating Voltage       | 2.7 V to 5.5 VDC  | 2.7 to 5.5 VDC  |
| Current Consumption     | Transmit: 200mW @ 110 mA, typ.<br>100mW @ 70 mA, typ.<br>Active (RX only): 10 mA, typ.<br>Stand-by: 120 µA<br>Power down: <1 µA | Transmit: 200mW @ 130 mA, typ.<br>100mW @ 70 mA, typ.<br>Active (RX only): 10 mA, typ.<br>Stand-by: 120 µA<br>Power down: <1 µA |
| Transmitter Power       | Adjustable power, 100mW or 200mW at 5 VDC   | Adjustable power, 100mW or 200mW at 5 VDC   |
| Transmitter Modulation  | ASK, adjustable 8% to 30% OOK   | ASK, adjustable 8% to 30% OOK   |
| Communication Interface | Parallel 8-bit or 4-wire SPI  | Parallel 8-bit or 4-wire SPI  |
| Operating Temperature   | -40°C to +110°C   | -40°C to +110°C   |
| Storage Temperature     | -55°C to +150°C   | -55°C to +150°C   |
| Package                 | 32 Pin QFN, (5 mm X 5 mm)   | 32 Pin QFN, (5 mm X 5 mm)   |
| Packing / Delivery      | Tape-on Reel, 250 or 3000 per reel  | Tape-on Reel, 250 or 3000 per reel  |

## LF Reader Types

| Part Number         | RI-RFM-006A           | RI-TMS3705A1          | DRG4               | RI-STU-MRD1          | RI-STU-251B   |
|---------------------|-----------------------|-----------------------|--------------------|----------------------|---------------|
| Type                | IC (SO 16)            | IC (SO 16)            | Reader Module      |                      | Reader/Writer |
| Typical Read Range* | up to 20 cm           | up to 20 cm           | up to 30 cm        |                      | up to 200 cm  |
| Interface           | I/O                   | I/O                   | (RS232, TTL level) |                      | RS232/422/485 |
| Operating Frequency | 134.2 kHz             | 134.2 kHz             | 134.2 kHz          |                      | 134.2 kHz     |
| Operating Voltage   | 3.5Vdc...5.5Vdc       | 4.5Vdc...5.5Vdc       | 5Vdc               |                      | 10Vdc...24Vdc |
| Part Number         | RI-RFM-003B           | RI-RFM-007B           | RI-RFM-008B        | RI-ACC-008B          |               |
| Type                | Mini RFM Module       | High Performance RFM  | Remote Antenna RFM | Antenna Tuning Board |               |
| Typical Read Range* | up to 60 cm           | up to 200 cm          | up to 200 cm       | up to 200 cm         |               |
| Interface           | I/O**                 | I/O**                 | I/O**              | Antenna Terminals    |               |
| Operating Frequency | 134.2 kHz             | 134.2 kHz             | 134.2 kHz          | 134.2 kHz            |               |
| Operating Voltage   | 5Vdc                  | 7Vdc...24Vdc          | 7Vdc...24Vdc       |                      |               |
| Part Number         | RI-CTL-MB2B           | RI-CTL-MB6B           |                    |                      |               |
| Type                | Digital Contr. Module | Digital Contr. Module |                    |                      |               |
| Typical Read Range* |                       |                       |                    |                      |               |
| Interface           | RS232, USB            | RS422/485, USB        |                    |                      |               |
| Operating Frequency |                       |                       |                    |                      |               |
| Operating Voltage   | 7Vdc...25Vdc          | 7Vdc...25Vdc          |                    |                      |               |

## LF Transponders

| Part Number            | RI-TRP-R9BK, RI-TRP-W9WK,<br>RI-TRP-M9WK                      | RI-TRP-RR3P, RI-TRP-WR3P<br>RI-TRP-REHP, RI-TRP-WEHP | RI-INL-RR2B, RI-TRP-WR2B<br>RI-INL-DR2B, RI-TRP-RE2B/WE2B | RI-INL-R9QM<br>RI-INL-W9QM   |
|------------------------|---|--|---|------------------------------|
| Type                   | 12 mm Wedge   | 23 mm Glass  | 32 mm Glass   | 24 mm Disk                   |
| Memory types available | R/O (64 bit), R/W (80 bit)<br>Multi (32 bit UID, 208 bit R/W) | R/O (64 bit)<br>RW (80 bit)                          | R/O (64 bit), R/W (80 bit)<br>MPT (1360 bit)              | R/O (64 bit)<br>R/W (80 bit) |
| Typical Read Range*    | up to 20 cm   | up to 60 cm  | up to 100 cm  | up to 50 cm                  |
| Operating Frequency    | 134.2 kHz   | 134.2 kHz  | 134.2 kHz   | 134.2 kHz                    |
| Dimensions             | 12 x 6 x 3 mm   | 3.85 x 23.1 mm                                       | 3.85 x 31.2 mm  | 24 mm dia.                   |
| Protection Class       | IP68  | Hermetically Sealed                                  | Hermetically Sealed                                       |                              |
| Case Material          | Plastic Compound  | Glass  | Glass   |                              |

\* Dependent on the configuration used, the RF regulation in country of use and the environmental condition

\*\* Modules RI-CTL-MB2B/RI-CTL-MB6B have to be combined with RFM modules

## LF Transponders (Continued)

| Part Number            | RI-TRP-R9QL<br>RI-TRP-W9QL                  | RI-TRP-R9UR<br>RI-TRP-W9UR                   | RI-TRP-RFOB<br>RI-TRP-WFOB                  | RI-TRP-R4FF<br>RI-TRP-W4FF                   | RI-TRP-R9TD<br>RI-TRP-W9TD                   |
|------------------------|---|--|---|--|--|
| Type                   | 30 mm Disk                                  | 85 mm Disk                                   | Keyring Tag                                 | Card   | 120 mm Cylindrical                           |
| Memory types available | R/O (64 bit)<br>R/W (80 bit)<br>up to 60 cm | R/O (64 bit)<br>R/W (80 bit)<br>up to 150 cm | R/O (64 bit)<br>R/W (80 bit)<br>up to 60 cm | R/O (64 bit)<br>R/W (80 bit)<br>up to 100 cm | R/O (64 bit)<br>R/W (80 bit)<br>up to 200 cm |
| Typical Read Range*    | 134.2 kHz                                   | 134.2 kHz                                    | 134.2 kHz                                   | 134.2 kHz                                    | 134.2 kHz                                    |
| Operating Frequency    | 29.4 x 8.4 mm                               | 85.5 x 5.5 mm                                | 10.5 x 37.5 mm                              | 85.5 x 54 x 1.3 mm                           | 21 x 121 mm                                  |
| Dimensions             | IP67  | IP53   | Hermetically Sealed                         | ISO 7810                                     | IP67   |
| Protection Class       | POM   | ASA  | ABS, Glass                                  | PVC  | PEI  |
| Case Material          |   |  |   |  |  |

## HF Packaged Transponders

| Part Number         | RF-HDT-DVBE-N0                          | RF-HDT-DVBB-N1                          | RF-TH1-CB1A                                    |
|---------------------|---|---|--|
| Type                | 22 mm Coin Overmolded                   | 22 mm Coin Overmolded                   | Vicinity Card                                  |
| Available Memory    | 256 bits organized in 8 x 32-bit blocks | 2k bits organized in 64 x 32-bit blocks |  |
| Operating Frequency | 13.56 MHz ± 300 kHz                     | 13.56 MHz ± 300 kHz                     | 13.56 MHz                                      |
| Dimensions          | Ø 22 ± 0.2 mm x 3 ± 0.2 mm              | Ø 22 ± 0.2 mm x 3 ± 0.2 mm              | 85.6 mm x 54 mm x 0.76 mm (according ISO 7810) |
| Case Material       | PPS, black                              | PPS, black                              | PVC (Polyvinylchloride), white                 |

## Tag-it™ HF-I Plus Transponders Inlay

| Part Number                              | RI-I11-112A-03<br>(square)                                    | RI-I11-112B-03<br>(square) | RI-I02-112A-03<br>(rectangle-lg) | RI-I02-112B-03<br>(rectangle-lg) | RI-I03-112A-03<br>(rectangle-mini) | RI-I15-112B-03<br>(rectangle-med) | RI-I16-112A-03<br>(circular) | RI-I17-112A-03<br>(CD/DVD) |
|--|---|----------------------------|----------------------------------|----------------------------------|------------------------------------|-----------------------------------|------------------------------|----------------------------|
| Supported Standards                      | ISO 15693, ISO/IEC 18000-3 (Mode 1)                           |                            |                                  |                                  |                                    |                                   |                              |                            |
| Available Memory                         | 2k bits organized in 64 x 32-bit blocks                       |                            |                                  |                                  |                                    |                                   |                              |                            |
| Factory Programmed                       | 64 bits   |                            |                                  |                                  |                                    |                                   |                              |                            |
| Resource Frequency                       | 13.86 MHz   | 14.4 MHz                   | 13.86 MHz                        | 14.4 MHz                         | 13.86 MHz                          | 14.1 MHz                          | 13.7 MHz                     | 13.8 MHz                   |
| Frequency Offset for Lamination Material | Paper   | PVC                        | Paper                            | PVC                              | Paper/PVC                          | Paper/PVC                         | Paper/PVC                    | Paper/PVC                  |
| Antenna Size (mm)                        | 45 x 45   | 45 x 45                    | 45 x 76                          | 45 x 76                          | 22.5 x 38                          | 34 x 65                           | Ø 24.2                       | Ø 32.5                     |
| Foil Width (mm)                          | 48 mm ± 0.5 mm  |                            |                                  |                                  |                                    |                                   |                              |                            |
| Delivery                                 | Single row tape with 48-mm foil width wound on cardboard reel |                            |                                  |                                  |                                    |                                   |                              |                            |

## Tag-it™ HF-I Pro Transponder Inlays Features - Password Write/Password Kill Functionality

| Part Number                              | RI-I11-114A-S1<br>(square)                                    | RI-I11-114B-S1<br>(square) | RI-I02-114A-S1<br>(rectangle-lg) | RI-I02-114B-S1<br>(rectangle-lg) | RI-I03-114A-S1<br>(rectangle-mini) | RI-I16-114A-S1<br>(circular) | RI-I17-114A-S1<br>(CD/DVD) |
|--|---|----------------------------|----------------------------------|----------------------------------|------------------------------------|------------------------------|----------------------------|
| Supported Standards                      | ISO 15693, ISO/IEC 18000-3 (Mode 1)                           |                            |                                  |                                  |                                    |                              |                            |
| Available Memory                         | 256 bits organized in 8 x 32-bit blocks                       |                            |                                  |                                  |                                    |                              |                            |
| Factory Programmed                       | 64 bits   |                            |                                  |                                  |                                    |                              |                            |
| Resource Frequency                       | 13.86 MHz   | 14.4 MHz                   | 13.86 MHz                        | 14.4 MHz                         | 13.86 MHz                          | 13.7 MHz                     | 13.8 MHz                   |
| Frequency Offset for Lamination Material | Paper   | PVC                        | Paper                            | PVC                              | Paper/PVC                          | Paper/PVC                    | Paper/PVC                  |
| Antenna Size (mm)                        | 45 x 45   | 45 x 45                    | 45 x 76                          | 45 x 76                          | 22.5 x 38                          | Ø 24.2                       | Ø 32.5                     |
| Foil Width (mm)                          | 48 mm ± 0.5 mm  |                            |                                  |                                  |                                    |                              |                            |
| Delivery                                 | Single row tape with 48-mm foil width wound on cardboard reel |                            |                                  |                                  |                                    |                              |                            |

## Tag-it™ HF-I Standard Transponder Inlays

| Part Number                              | RI-I11-114A-01<br>(square)                                    | RI-I11-114B-01<br>(square) | RI-I02-114A-01<br>(rectangle-lg) | RI-I02-114B-01<br>(rectangle-lg) | RI-I03-114-01<br>(rectangle-mini) | RI-I16-114A-01<br>(circular) | RI-I17-114A-01<br>(CD/DVD) |
|--|---|----------------------------|----------------------------------|----------------------------------|-----------------------------------|------------------------------|----------------------------|
| Supported Standards                      | ISO 15693, ISO 18000-3  |                            |                                  |                                  |                                   |                              |                            |
| Available Memory                         | 256 bits organized in 8 x 32-bit blocks                       |                            |                                  |                                  |                                   |                              |                            |
| Factory Programmed                       | 64 bits   |                            |                                  |                                  |                                   |                              |                            |
| Resource Frequency                       | 13.86 MHz   | 14.2 MHz                   | 13.86 MHz                        | 14.4 MHz                         | 13.86 MHz                         | 13.7 MHz                     | 13.8 MHz                   |
| Frequency Offset for Lamination Material | Paper   | PVC                        | Paper                            | PVC                              | Paper/PVC                         | Paper/PVC                    | Paper/PVC                  |
| Antenna Size (mm)                        | 45 x 45   | 45 x 45                    | 45 x 76                          | 45 x 76                          | 22.5 x 38                         | Ø 24.2                       | Ø 32.5                     |
| Foil Width (mm)                          | 48 mm ± 0.5 mm  |                            |                                  |                                  |                                   |                              |                            |
| Delivery                                 | Single row tape with 48-mm foil width wound on cardboard reel |                            |                                  |                                  |                                   |                              |                            |

## Tag-it™ HF-I Family Die

| Part number             | RF-HDT-AJLC-G0<br>RF-HDT-SJLC-G0           | RF-HDT-AJLE-G1<br>RF-HDT-SJLE-G1           | RF-HDT-AJLS-G1<br>RF-HDT-SJLS-G1           |
|-------------------------|--|--|--|
| HF-I Family             | Plus                                       | Standard                                   | Pro  |
| Die Supported Standards | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) |
| Available Memory        | 2k bits organized in 64 x 32-bit blocks    | 256 bits organized in 8 x 32-bit blocks    | 256 bits organized in 8 x 32-bit blocks    |
| Die Thickness           | 150µm / 265µm                              | 150µm / 150µm                              | 150µm / 265µm                              |
| Wafer Processing        | Bumped, Sawm, Grinded, Inked               | Bumped, Sawm, Grinded, Inked               | Bumped, Sawm, Grinded, Inked               |
| Bump Material           | Gold (AU)/Nickel-Gold (AU-NI)              | Gold (AU)/Nickel-Gold (AU-NI)              | Gold (AU)/Nickel-Gold (AU-NI)              |
| Part number             | RF-HDT-WNMC-M0                             | RF-HDT-SNLE-G1                             | RF-HDT-WNME-M0                             |
| HF-I Family             | Plus                                       | Standard                                   | Standard                                   |
| Die Supported Standards | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) | ISO/IEC 15693;<br>ISO/IEC 18000-3 (Mode 1) |
| Available Memory        | 2k bits organized in 64 x 32-bit blocks    | 256 bits organized in 8 x 32-bit blocks    | 256 bits organized in 8 x 32-bit blocks    |
| Die Thickness           | 710-740µm                                  | 150µm                                      | 710-740µm                                  |
| Wafer Processing        | Unprocessed                                | Sawn, Grinded, Inked                       | Unprocessed                                |
| Bump Material           | -  | -  | -  |

## UHF Family

| Part Number            | RI-UHF-00001-01                              | RI-UHF-11111-01            | RI-UHF-STRAP-08         |
|------------------------|--|----------------------------|-------------------------|
| Type                   | IC - Unprocessed Wafer                       | IC - Bumped, Sawed, Framed | Strap                   |
| IC Supported Standard  | EPC C1G2 and ISO/IEC 18000-6c                |                            |                         |
| IC Operating Frequency | 860-960Mhz                                   |                            |                         |
| EPC Memory             | 96 bits EPC user programmable                |                            |                         |
| TID Memory             | 32 bits factory pre-programmed               |                            |                         |
| Data Retention         | 10 years at +25°C                            |                            |                         |
| Write/Erase Cycles     | 100000 +25°C preliminary                     |                            |                         |
| Operating Temperature  | -40°C to 65°C (Read), -25°C to +65°C (Write) |                            |                         |
| Strap Pitch            |  |                            | 4.0mm (+0.1mm, -0.4 mm) |
| Width of Strap         |  |                            | 9.0mm (+/- 0.25 mm)     |
| Material/Thickness     | 710-740um                                    | 150um                      | 50um PET substrate      |
| Quantity               | >40,000 IC/wafer                             | >40,000 IC/wafer           | 40,000 per Reel         |

[www.ti.com/rfid](http://www.ti.com/rfid)

## TI RFID Worldwide Technical Support

### Internet

#### TI RFID Home Page

[www.ti.com/rfid](http://www.ti.com/rfid)

### Product Information Centers

#### US and Canada

Phone 800-962-7343  
Fax: 214-567-7343

Business Hours (Central Standard Time):  
Monday - Friday 8:00 am - 5:00 pm  
E-mail: [rfidsupport@ti.com](mailto:rfidsupport@ti.com)

Texas Instruments  
Radio Frequency Identification System  
6550 Chase Oaks Blvd., MS 8470  
Plano, Texas 75023  
USA

#### Europe, Middle East and Africa (EMEA)

European Toll Free\* 00800 275 83927  
International +49 (0) 8161 80 2121  
Russian Support +7 (495) 981 07 01

\*The European Toll Free number is not active in all countries. If you have technical difficulty calling the toll free number please use the international number  
Fax: +49 (0) 8161 80 2045

Business Hours (Central European Time):  
Monday - Wednesday 10:00 - 18:00  
Tuesday - Thursday 09:00 - 18:00  
Friday 09:00 - 16:00  
E-mail: [rfidsupport@ti.com](mailto:rfidsupport@ti.com)

Texas Instruments Deutschland GmbH  
RFID Systems  
Haggertystrasse 1  
D-85350 Freising  
Germany

**Important Notice:** The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

The platform bar and Tag-it are trademarks of Texas Instruments.  
All other trademarks are the property of their respective owners.

RFID010208A