





CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



TERM. NO.'s FOR REF. ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	3-4 @20°C	0.220 ohms ±10%
D.C. RESISTANCE	10-8 @20°C	28.50 ohms ±10%
D.C. RESISTANCE	9-7 @20°C	28.50 ohms ±10%
INDUCTANCE	3-4 50kHz, 100mVAC, Ls	100uH ±10%
SATURATION CURRENT	20% rolloff from initial	2ADC
LEAKAGE INDUCTANCE	3-4 tie(7+8+9+10), 100kHz, 10mVAC, Ls	3.0uH max.
INTERWINDING CAPACITANCE	3-10 tie(8+9), 100kHz, 100mVAC, Cs	30pF max.
DIELECTRIC	3-10 tie(8+9), 1500VAC, 1 second	-
URNS RATIO	(10-8):(3-4)	10:1, ±2%
URNS RATIO	(9-7):(3-4)	10:1, ±2%

GENERAL SPECIFICATIONS:
OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0499 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE TRANSFORMER	PART NO. 750311681
6A	4/11	SEE REVISION SHEET FOR REVISION LEVEL		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eISos p/n: 750311681	SPECIFICATION SHEET 1 OF 1