



#### General ordering data

Order No.	1857560500
Part designation	SAIL-M8W-4-5.0U
Version	Sensor/Actuator line, One end without connector, LED: No, 5.00 m, PUR/PVC
EAN	4032248479443
Qty.	1 pc(s).

#### Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-30 °C
Cable diameter, max.	5.4 mm
Cable diameter, min	5 mm
Connection cross-section	0,25
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M8
Core cross-section	0.25 mm <sup>2</sup>
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	60 V DC
Sheathing colour	black
Suitable for cable carriers	Yes
Wiring diagram	
No. of poles	4
Version	pin, 90°
Cable length	5 m

#### Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

## Classifications

### Similar products

Order No.	Part designation	Version
1857560100	SAIL-M8W-4-1.0U	Sensor/Actuator line, One end without connector, LED: No, 1.00 m, PUR/PVC
1857560150	SAIL-M8W-4-1.5U	Sensor/Actuator line, One end without connector, LED: No, 1.50 m, PUR/PVC
1857561000	SAIL-M8W-4-10U	Sensor/Actuator line, One end without connector, LED: No, 10.00 m, PUR/PVC
1857560300	SAIL-M8W-4-3.0U	Sensor/Actuator line, One end without connector, LED: No, 3.00 m, PUR/PVC