



General ordering data

Order No.	1927210500
Part designation	SAIL-M8WM8W-3-5.0V
Version	Sensor/Actuator line, Connecting line, LED: No, 5.00 m, PVC/PVC
EAN	4032248575350
Qty.	1 pc(s).

Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-30 °C
Cable diameter, max.	4.8 mm
Cable diameter, min	4.4 mm
Connection cross-section	0,25
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M8
Core cross-section	0.25 mm ²
Material	PVC/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	60 V DC
Sheathing colour	black
Wiring diagram jumped	No
No. of poles	3
Version	pin, 90° - socket 90°
Cable length	5 m

Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

Classifications

Similar products

Order No.	Part designation	Version
1927210150	SAIL-M8WM8W-3-1.5V	Sensor/Actuator line, Connecting line, LED: No, 1.50 m, PVC/PVC
1927211000	SAIL-M8WM8W-3-10V	Sensor/Actuator line, Connecting line, LED: No, 10.00 m, PVC/PVC
1927210300	SAIL-M8WM8W-3-3.0V	Sensor/Actuator line, Connecting line, LED: No, 3.00 m, PVC/PVC