





1. Mechanical Dimensions:




(BOTTOM VIEW)



(SUGGESTED MOUNTING PAD)

2. Schematic:



3. Electrical Specifications:@25°C

INDUCTANCE: 100.0uH ±20% @100KHz 0.1V

DC RESISTANCE: 0.308 Ohms Max

CURRENT: 1.2 ADC Max

Notes:

1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible

DOC REV A/2

XFMR5 Inc.	Title: XFTPRH1204 SERIES INDUCTORS								
	UNLESS OTHERWISE SPECIFIED TOLERANCES: TYPICAL Dimensions in MM	<table border="1"> <tr> <td>P/N: XFTPRH1204-101M</td> <td>REV. A</td> </tr> <tr> <td>DWN.</td> <td>廖玉坤</td> </tr> <tr> <td>CHK.</td> <td>李清儿</td> </tr> <tr> <td>APP.</td> <td>BW</td> </tr> </table>	P/N: XFTPRH1204-101M	REV. A	DWN.	廖玉坤	CHK.	李清儿	APP.
P/N: XFTPRH1204-101M	REV. A								
DWN.	廖玉坤								
CHK.	李清儿								
APP.	BW								

THIS DOCUMENT IS STRICTLY NOT ALLOWED TO BE DUPLICATED WITHOUT AUTHORIZATION

SHEET 1 OF 1

Apr-10-03

Apr-10-03

Apr-10-03